



International  
Organization for  
Standardization

Snap-shot of the  
**ISO 11783-11 online data base**

<b>DD Entity</b>	<b>0 - Data Dictionary Version</b>
Definition	This DDE is used to specify which version of the Data Dictionary is being used.
Comment	This DDE was a result of Jan 2005 Task Controller meeting.
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	11783-Part 10 Task Force
Submit Date	2005-01-20
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>1 - Setpoint Volume Per Area Application Rate</b>
Definition	Setpoint Application Rate specified as volume per area
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /m <sup>2</sup> - Capacity per area unit
Resolution	0,01
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,00 - 21474836,47
Submit by	Part 10 Task Force
Submit Date	0000-00-00
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>2 - Actual Volume Per Area Application Rate</b>
Definition	Actual Application Rate specified as volume per area
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /m <sup>2</sup> - Capacity per area unit
Resolution	0,01
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,00 - 21474836,47
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>3 - Default Volume Per Area Application Rate</b>
Definition	Default Application Rate specified as volume per area
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /m <sup>2</sup> - Capacity per area unit
Resolution	0,01
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,00 - 21474836,47
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	4 - Minimum Volume Per Area Application Rate
Definition	Minimum Application Rate specified as volume per area
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /m <sup>2</sup> - Capacity per area unit
Resolution	0,01
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,00 - 21474836,47
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	5 - Maximum Volume Per Area Application Rate
Definition	Maximum Application Rate specified as volume per area
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /m <sup>2</sup> - Capacity per area unit
Resolution	0,01
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,00 - 21474836,47
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>6 - Setpoint Mass Per Area Application Rate</b>
Definition	Setpoint Application Rate specified as mass per area
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>7 - Actual Mass Per Area Application Rate</b>
Definition	Actual Application Rate specified as mass per area
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>8 - Default Mass Per Area Application Rate</b>
Definition	Default Application Rate specified as mass per area
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>9 - Minimum Mass Per Area Application Rate</b>
Definition	Minimum Application Rate specified as mass per area
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>10 - Maximum Mass Per Area Application Rate</b>
Definition	Maximum Application Rate specified as mass per area
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>11 - Setpoint Count Per Area Application Rate</b>
Definition	Setpoint Application Rate specified as count per area
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	/m <sup>2</sup> - Quantity per area unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>12 - Actual Count Per Area Application Rate</b>
Definition	Actual Application Rate specified as count per area
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	/m <sup>2</sup> - Quantity per area unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>13 - Default Count Per Area Application Rate</b>
Definition	Default Application Rate specified as count per area
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	/m <sup>2</sup> - Quantity per area unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.



DD Entity	14 - Minimum Count Per Area Application Rate
Definition	Minimum Application Rate specified as count per area
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	/m <sup>2</sup> - Quantity per area unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	15 - Maximum Count Per Area Application Rate
Definition	Maximum Application Rate specified as count per area
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	/m <sup>2</sup> - Quantity per area unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>16 - Setpoint Spacing Application Rate</b>
Definition	Setpoint Application Rate specified as distance: e.g. seed spacing of a precision seeder
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>17 - Actual Spacing Application Rate</b>
Definition	Actual Application Rate specified as distance: e.g. seed spacing of a precision seeder
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>18 - Default Spacing Application Rate</b>
Definition	Default Application Rate specified as distance: e.g. seed spacing of a precision seeder
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>19 - Minimum Spacing Application Rate</b>
Definition	Minimum Application Rate specified as distance: e.g. seed spacing of a precision seeder
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	20 - Maximum Spacing Application Rate
Definition	Maximum Application Rate specified as distance: e.g. seed spacing of a precision seeder
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	21 - Setpoint Volume Per Volume Application Rate
Definition	Setpoint Application Rate specified as volume per volume
Comment	
Typically used by Device Class(es)	5 - Fertilizer 6 - Sprayers
Unit Symbol	mm <sup>3</sup> /m <sup>3</sup> - Capacity per capacity unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	22 - Actual Volume Per Volume Application Rate
Definition	Actual Application Rate specified as volume per volume
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /m <sup>3</sup> - Capacity per capacity unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	23 - Default Volume Per Volume Application Rate
Definition	Default Application Rate specified as volume per volume
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /m <sup>3</sup> - Capacity per capacity unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>24 - Minimum Volume Per Volume Application Rate</b>
Definition	Minimum Application Rate specified as volume per volume
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /m <sup>3</sup> - Capacity per capacity unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>25 - Maximum Volume Per Volume Application Rate</b>
Definition	Maximum Application Rate specified as volume per volume
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /m <sup>3</sup> - Capacity per capacity unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>26 - Setpoint Mass Per Mass Application Rate</b>
Definition	Setpoint Application Rate specified as mass per mass
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	mg/kg - Mass per mass unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>27 - Actual Mass Per Mass Application Rate</b>
Definition	Actual Application Rate specified as mass per mass
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	mg/kg - Mass per mass unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>28 - Default Mass Per Mass Application Rate</b>
Definition	Default Application Rate specified as mass per mass
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/kg - Mass per mass unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>29 - Minimum Mass Per Mass Application Rate</b>
Definition	Minimum Application Rate specified as mass per mass
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/kg - Mass per mass unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.



<b>DD Entity</b>	<b>30 - MaximumMass Per Mass Application Rate</b>
Definition	Maximum Application Rate specified as mass per mass
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/kg - Mass per mass unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>31 - Setpoint Volume Per Mass Application Rate</b>
Definition	Setpoint Application Rate specified as volume per mass
Comment	
Typically used by Device Class(es)	5 - Fertilizer 6 - Sprayers
Unit Symbol	mm <sup>3</sup> /kg - Capacity per mass unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	32 - Actual Volume Per Mass Application Rate
Definition	Actual Application Rate specified as volume per mass
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 9 - Forage harvester
Unit Symbol	mm <sup>3</sup> /kg - Capacity per mass unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	Added device class 9 - Forage Harvester

DD Entity	33 - Default Volume Per Mass Application Rate
Definition	Default Application Rate specified as volume per mass
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /kg - Capacity per mass unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>34 - Minimum Volume Per Mass Application Rate</b>
Definition	Minimum Application Rate specified as volume per mass
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /kg - Capacity per mass unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>35 - Maximum Volume Per Mass Application Rate</b>
Definition	Maximum Application Rate specified as volume per mass
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /kg - Capacity per mass unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>36 - Setpoint Volume Per Time Application Rate</b>
Definition	Setpoint Application Rate specified as volume per time
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /s - Flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>37 - Actual Volume Per Time Application Rate</b>
Definition	Actual Application Rate specified as volume per time
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /s - Flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	38 - Default Volume Per Time Application Rate
Definition	Default Application Rate specified as volume per time
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /s - Flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	39 - Minimum Volume Per Time Application Rate
Definition	Minimum Application Rate specified as volume per time
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /s - Flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>40 - Maximum Volume Per Time Application Rate</b>
Definition	Maximum Application Rate specified as volume per time
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mm <sup>3</sup> /s - Flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>41 - Setpoint Mass Per Time Application Rate</b>
Definition	Setpoint Application Rate specified as mass per time
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>42 - Actual Mass Per Time Application Rate</b>
Definition	Actual Application Rate specified as mass per time
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>43 - Default Mass Per Time Application Rate</b>
Definition	Default Application Rate specified as mass per time
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>44 - Minimum Mass Per Time Application Rate</b>
Definition	Minimum Application Rate specified as mass per time
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>45 - Maximum Mass Per Time Application Rate</b>
Definition	Maximum Application Rate specified as mass per time
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.



<b>DD Entity</b>	<b>46 - Setpoint Count Per Time Application Rate</b>
Definition	Setpoint Application Rate specified as count per time
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>47 - Actual Count Per Time Application Rate</b>
Definition	Actual Application Rate specified as count per time
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>48 - Default Count Per Time Application Rate</b>
Definition	Default Application Rate specified as count per time
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>49 - Minimum Count Per Time Application Rate</b>
Definition	Minimum Application Rate specified as count per time
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>50 - Maximum Count Per Time Application Rate</b>
Definition	Maximum Application Rate specified as count per time
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>51 - Setpoint Tillage Depth</b>
Definition	Setpoint Tillage Depth of Device Element below soil surface, value increases with depth. In case of a negative value the system will indicate the distance above the ground.
Comment	
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 8 - Root Harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	

<b>DD Entity</b>	<b>52 - Actual Tillage Depth</b>
Definition	Actual Tillage Depth of Device Element below soil surface, value increases with depth. In case of a negative value the system will indicate the distance above the ground.
Comment	
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	

<b>DD Entity</b>	<b>53 - Default Tillage Depth</b>
Definition	Default Tillage Depth of Device Element below soil surface, value increases with depth. In case of a negative value the system will indicate the distance above the ground.
Comment	Use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 8 - Root Harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	

<b>DD Entity</b>	<b>54 - Minimum Tillage Depth</b>
Definition	Minimum Tillage Depth of Device Element below soil surface, value increases with depth. In case of a negative value the system will indicate the distance above the ground.
Comment	Supplied by device as physical minimum
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 8 - Root Harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	

<b>DD Entity</b>	<b>55 - Maximum Tillage Depth</b>
Definition	Maximum Tillage Depth of Device Element below soil surface, value increases with depth. In case of a negative value the system will indicate the distance above the ground.
Comment	Supplied by device as physical maximum
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 8 - Root Harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	

<b>DD Entity</b>	<b>56 - Setpoint Seeding Depth</b>
Definition	Setpoint Seeding Depth of Device Element below soil surface, value increases with depth
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>57 - Actual Seeding Depth</b>
Definition	Actual Seeding Depth of Device Element below soil surface, value increases with depth
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>58 - Default Seeding Depth</b>
Definition	Default Seeding Depth of Device Element below soil surface, value increases with depth
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>59 - Minimum Seeding Depth</b>
Definition	Minimum Seeding Depth of Device Element below soil surface, value increases with depth
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>60 - Maximum Seeding Depth</b>
Definition	Maximum Seeding Depth of Device Element below soil surface, value increases with depth
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>61 - Setpoint Working Height</b>
Definition	Setpoint Working Height of Device Element above crop or soil
Comment	
Typically used by Device Class(es)	0 - Non-specific system 5 - Fertilizer 6 - Sprayers 7 - Harvesters 9 - Forage harvester 10 - Irrigation 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.



<b>DD Entity</b>	<b>62 - Actual Working Height</b>
Definition	Actual Working Height of Device Element above crop or soil
Comment	This is the height above the effective control surface. For sprayers this is the height above the crop canopy and for fertilizer spreaders, harvesters, etc it is the height above the ground.
Typically used by Device Class(es)	5 - Fertilizer 6 - Sprayers 7 - Harvesters 9 - Forage harvester 10 - Irrigation
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	Added comment for clarification.

<b>DD Entity</b>	<b>63 - Default Working Height</b>
Definition	Default Working Height of Device Element above crop or soil
Comment	use when missing Position data or outside any Treatment Zone
Typically used by Device Class(es)	5 - Fertilizer 6 - Sprayers 7 - Harvesters 9 - Forage harvester 10 - Irrigation
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>64 - Minimum Working Height</b>
Definition	Minimum Working Height of Device Element above crop or soil
Comment	supplied by device as physical minimum
Typically used by Device Class(es)	5 - Fertilizer 6 - Sprayers 7 - Harvesters 9 - Forage harvester 10 - Irrigation
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>65 - Maximum Working Height</b>
Definition	Maximum Working Height of Device Element above crop or soil
Comment	supplied by device as physical maximum
Typically used by Device Class(es)	5 - Fertilizer 6 - Sprayers 7 - Harvesters 9 - Forage harvester 10 - Irrigation
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	66 - Setpoint Working Width
Definition	Setpoint Working Width of Device Element
Comment	
Typically used by Device Class(es)	0 - Non-specific system 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 14 - Special Crops 15 - Municipal Work
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	67 - Actual Working Width
Definition	Actual Working Width of Device Element
Comment	This is the effective / active working width during operation.
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force

Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	Added comment for clarification.

<b>DD Entity</b>	<b>68 - Default Working Width</b>
Definition	Default Working Width of Device Element
Comment	
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>69 - Minimum Working Width</b>
Definition	Minimum Working Width of Device Element
Comment	
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1

Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>70 - Maximum Working Width</b>
Definition	Maximum Working Width of Device Element
Comment	
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>71 - Setpoint Volume Content</b>
Definition	Setpoint Device Element Content specified as volume
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	72 - Actual Volume Content
Definition	Actual Device Element Content specified as volume
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	73 - Maximum Volume Content
Definition	Maximum Device Element Content specified as volume
Comment	is a minimum needed as well ??
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02



Status Comments	DDEs have been moved to published for creating the new Annex A version.
-----------------	---

<b>DD Entity</b>	<b>74 - Setpoint Mass Content</b>
Definition	Setpoint Machine Element Content specified as mass
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>75 - Actual Mass Content</b>
Definition	Actual Device Element Content specified as mass
Comment	If the device is equipped with a weighing system which provides the possibility to tare the current load it is possible that the value has a negative sign in case of an unload operation.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	2

Current Status	ISO-Published
Status Date	2011-04-04
Status Comments	

DD Entity	76 - Maximum Mass Content
Definition	Maximum Device Element Content specified as mass
Comment	is a minimum needed as well ??
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	77 - Setpoint Count Content
Definition	Setpoint Device Element Content specified as count
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02

Status Comments	DDEs have been moved to published for creating the new Annex A version.
-----------------	---

<b>DD Entity</b>	<b>78 - Actual Count Content</b>
Definition	Actual Device Element Content specified as count
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>79 - Maximum Count Content</b>
Definition	Maximum Device Element Content specified as count
Comment	is a minimum needed as well ??
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>80 - Application Total Volume in [L]</b>
Definition	Accumulated Application specified as volume in liter [L]
Comment	is a counter of a device element
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	L - Capacity count
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>81 - Application Total Mass in [kg]</b>
Definition	Accumulated Application specified as mass in kilogram [kg]
Comment	is a counter of a device element
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>82 - Application Total Count</b>
Definition	Accumulated Application specified as count
Comment	is a counter of a device element
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>83 - Volume Per Area Yield</b>
Definition	Yield as volume per area
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	ml/m <sup>2</sup> - Capacity per area large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.



<b>DD Entity</b>	<b>84 - Mass Per Area Yield</b>
Definition	Yield as mass per area, not corrected for the reference moisture percentage DDI 184.
Comment	This Mass per Area yield is the mass that includes the actual percentage moisture (DDI 99) if this is measured on e.g. harvesting equipment. This comment is added to clarify and differentiate this DDI from the Dry Mass Per Area Yield (DDI 181).
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>85 - Count Per Area Yield</b>
Definition	Yield as count per area
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	/m <sup>2</sup> - Quantity per area unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>86 - Volume Per Time Yield</b>
Definition	Yield as volume per time
Comment	
Typically used by Device Class(es)	0 - Non-specific system
Unit Symbol	ml/s - Float large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>87 - Mass Per Time Yield</b>
Definition	Yield as mass per time, not corrected for the reference moisture percentage DDI 184.
Comment	This Mass per Time yield is the mass that includes the actual percentage moisture (DDI 99) if this is measured on e.g. harvesting equipment. This comment is added to clarify and differentiate this DDI from the Dry Mass Per Time Yield (DDI 182).
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>88 - Count Per Time Yield</b>
Definition	Yield as count per time
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>89 - Yield Total Volume</b>
Definition	Accumulated Yield specified as volume
Comment	is a counter of a machine element
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	L - Quantity per volume
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>90 - Yield Total Mass</b>
Definition	Accumulated Yield specified as mass, not corrected for the reference moisture percentage DDI 184.
Comment	This Yield Total Mass is the mass that includes the average percentage moisture (DDI 262) if this is measured on e.g. harvesting equipment. This comment is added to clarify and differentiate this DDI from the Yield Total Dry Mass (DDI 183).
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>91 - Yield Total Count</b>
Definition	Accumulated Yield specified as count
Comment	is a counter of a machine element
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>92 - Volume Per Area Crop Loss</b>
Definition	Crop yield loss as volume per area
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	ml/m <sup>2</sup> - Capacity per area large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>93 - Mass Per Area Crop Loss</b>
Definition	Crop yield loss as mass per area
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>94 - Count Per Area Crop Loss</b>
Definition	Crop yield loss as count per area
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	/m <sup>2</sup> - Quantity per area unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>95 - Volume Per Time Crop Loss</b>
Definition	Crop yield loss as volume per time
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	ml/s - Float large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>96 - Mass Per Time Crop Loss</b>
Definition	Crop yield loss as mass per time
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>97 - Count Per Time Crop Loss</b>
Definition	Crop yield loss as count per time
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>98 - Percentage Crop Loss</b>
Definition	Crop yield loss
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>99 - Crop Moisture</b>
Definition	Moisture in crop yield
Comment	This DDE defines the actual percentage moisture of the crop.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.



<b>DD Entity</b>	<b>100 - Crop Contamination</b>
Definition	Dirt or foreign material in crop yield
Comment	This DDE defines the contamination in ratio of the yield DDI units.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>101 - Setpoint Bale Width</b>
Definition	Setpoint Bale Width for square baler or round baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>102 - Actual Bale Width</b>
Definition	Actual Bale Width for square baler or round baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>103 - Default Bale Width</b>
Definition	Default Bale Width for square baler or round baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	104 - Minimum Bale Width
Definition	Minimum Bale Width for square baler or round baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	105 - Maximum Bale Width
Definition	Maximum Bale Width for square baler or round baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>106 - Setpoint Bale Height</b>
Definition	Setpoint Bale Height is only applicable to square baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>107 - ActualBaleHeight</b>
Definition	Actual Bale Height is only applicable to square baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>108 - Default Bale Height</b>
Definition	Default Bale Height is only applicable to square baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>109 - Minimum Bale Height</b>
Definition	Minimum Bale Height is only applicable to square baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>110 - Maximum Bale Height</b>
Definition	Maximum Bale Height is only applicable to square baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>111 - Setpoint Bale Size</b>
Definition	Setpoint Bale Size as length for a square baler or diameter for a round baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>112 - Actual Bale Size</b>
Definition	Actual Bale Size as length for a square baler or diameter for a round baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>113 - Default Bale Size</b>
Definition	Default Bale Size as length for a square baler or diameter for a round baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>114 - Minimum Bale Size</b>
Definition	Minimum Bale Size as length for a square baler or diameter for a round baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>115 - Maximum Bale Size</b>
Definition	Maximum Bale Size as length for a square baler or diameter for a round baler
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.



DD Entity	116 - Total Area
Definition	Accumulated Area
Comment	is a counter of a machine element
Typically used by Device Class(es)	0 - Non-specific system 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 14 - Special Crops 15 - Municipal Work
Unit Symbol	m <sup>2</sup> - Area
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	117 - Effective Total Distance
Definition	Accumulated Distance in working position
Comment	is a counter of a machine element
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647

Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>118 - Ineffective Total Distance</b>
Definition	Accumulated Distance out of working position
Comment	is a counter of a machine element
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>119 - Effective Total Time</b>
Definition	Accumulated Time in working position
Comment	is a counter of a machine element
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 17 - Sensor System
Unit Symbol	s - Time count

Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	2
Current Status	ISO-Published
Status Date	2011-12-21
Status Comments	

DD Entity	120 - Ineffective Total Time
Definition	Accumulated Time out of working position
Comment	is a counter of a machine element
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	s - Time count
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	121 - Product Density Mass Per Volume
Definition	Product Density as mass per volume
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	mg/l - Mass per capacity unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647

Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>122 - Product Density Mass PerCount</b>
Definition	Product Density as mass per count
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	mg/1000 - 1000 seed Mass
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>123 - Product Density Volume Per Count</b>
Definition	Product Density as volume per count
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	ml/1000 - Volume per quantity unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2003-08-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02

Status Comments	DDEs have been moved to published for creating the new Annex A version.
-----------------	---



<b>DD Entity</b>	<b>124 - Auxiliary Valve Scaling Extend</b>
Definition	Factor to apply to AuxValveCommand PortFlowCommand. The scaling of the port flow relates to flow, not to spool position, although the position of the spool is of course indirectly affected.
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	% - Percent
Resolution	0,1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Lars Althof
Submit Date	2004-09-10
Submit Company	57 - Sauer-Danfoss Co.
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>125 - Auxiliary Valve Scaling Retract</b>
Definition	Factor to apply to AuxValveCommand PortFlowCommand. The scaling of the port flow relates to flow, not to spool position, although the position of the spool is of course indirectly affected.
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	% - Percent
Resolution	0,1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Lars Althof
Submit Date	2004-09-10
Submit Company	57 - Sauer-Danfoss Co.
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	126 - Auxiliary Valve Ramp Extend Up
Definition	The valve will apply a ramp to the Auxiliary ValveCommand PortFlowCommand, to limit the acceleration or deceleration of flow. The valve must apply the ramp to create a linear increase/decrease of flow over time.
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	ms - Time
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Lars Althof
Submit Date	2004-09-10
Submit Company	57 - Sauer-Danfoss Co.
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	127 - Auxiliary Valve Ramp Extend Down
Definition	The valve will apply a ramp to the Auxiliary ValveCommand PortFlowCommand, to limit the acceleration or deceleration of flow. The valve must apply the ramp to create a linear increase/decrease of flow over time.
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	ms - Time
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Lars Althof
Submit Date	2004-09-10
Submit Company	57 - Sauer-Danfoss Co.
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	128 - Auxiliary Valve Ramp Retract Up
Definition	The valve will apply a ramp to theAuxiliary ValveCommand PortFlowCommand, to limit the acceleration or deceleration of flow. The valve must apply the ramp to create a linear increase/decrease of flow over time.
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	ms - Time
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Lars Althof
Submit Date	2004-09-10
Submit Company	57 - Sauer-Danfoss Co.
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	129 - Auxiliary Valve Ramp Retract Down
Definition	The valve will apply a ramp to the Auxiliary ValveCommand PortFlowCommand, to limit the acceleration or deceleration of flow. The valve must apply the ramp to create a linear increase/decrease of flow over time.
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	ms - Time
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Lars Althof
Submit Date	2004-09-10
Submit Company	57 - Sauer-Danfoss Co.
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>130 - Auxiliary Valve Float Threshold</b>
Definition	Safety function. Current output of valve must be above threshold before float command is allowed.
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	% - Percent
Resolution	0,1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Lars Althof
Submit Date	2004-09-10
Submit Company	57 - Sauer-Danfoss Co.
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>131 - Auxiliary Valve Progressivity Extend</b>
Definition	Define non-linear relationship between command and flow by 2nd degree polynomium. (I will get polynomium)
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	n.a. -
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Lars Althof
Submit Date	2004-09-10
Submit Company	57 - Sauer-Danfoss Co.
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>132 - Auxiliary Valve Progressivity Retract</b>
Definition	Define non-linear relationship between command and flow by 2nd degree polynomium. (I will get polynomium)
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	n.a. -
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Lars Althof
Submit Date	2004-09-10
Submit Company	57 - Sauer-Danfoss Co.
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>133 - Auxiliary Valve Invert Ports</b>
Definition	Tell valve to swap extend and retract ports, easier than redoing plumbing on valve
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	n.a. -
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Lars Althof
Submit Date	2004-09-10
Submit Company	57 - Sauer-Danfoss Co.
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>134 - Device Element Offset X</b>
Definition	X direction offset of a DeviceElement relative to a Device.
Comment	This DDE was a result of Jan 2005 Task Controller meeting.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	11783-Part 10 Task Force
Submit Date	2005-01-20
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>135 - Device Element Offset Y</b>
Definition	Y direction offset of a DeviceElement relative to a Device.
Comment	This DDE was a result of Jan 2005 Task Controller meeting.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647

Submit by	11783-Part 10 Task Force
Submit Date	2005-01-20
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	136 - Device Element Offset Z
Definition	Z direction offset of a DeviceElement relative to a Device.
Comment	This DDE was a result of Jan 2005 Task Controller meeting.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	mm - Length
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	11783-Part 10 Task Force
Submit Date	2005-01-20
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

DD Entity	137 - Device Volume Capacity
Definition	DeviceElement Volume Capacity, dimension of a DeviceElement
Comment	This DDE was a result of Jan 2005 Task Controller meeting.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	11783-Part 10 Task Force
Submit Date	2005-01-20
Submit Company	89 - Kverneland Group, Electronics Division



Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>138 - Device Mass Capacity</b>
Definition	DeviceElement Mass Capacity, dimension of a DeviceElement
Comment	This DDE was a result of Jan 2005 Task Controller meeting.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	11783-Part 10 Task Force
Submit Date	2005-01-20
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>139 - Device Count Capacity</b>
Definition	DeviceElement Count Capacity, dimension of a DeviceElement
Comment	This DDE was a result of Jan 2005 Task Controller meeting.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	11783-Part 10 Task Force
Submit Date	2005-01-20
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-02-02

Status Comments	DDEs have been moved to published for creating the new Annex A version.
-----------------	---

<b>DD Entity</b>	<b>140 - Setpoint Percentage Application Rate</b>
Definition	Application Rate expressed as percentage
Comment	This DDE was a result of Jan 2005 Task Controller meeting.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	11783-Part 10 Task Force
Submit Date	2005-01-20
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2015-01-26
Status Comments	

<b>DD Entity</b>	<b>141 - Actual Work State</b>
Definition	Actual Work State, 2 bits defined as 00=disabled/off, 01=enabled/on, 10=error, 11=undefined/not installed
Comment	<p>See the DDI 290 attachment "ISO11783-11-DDI-289-SetpointWorkState" as reference for implementation guideline.</p> <p>This DDE has been revised in 2012 to be used as the Actual Work State. A separate Setpoint Work State was added to the data dictionary at that time.</p> <p>Original comment: this DDE was a result of March 2005 TF10 meeting.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	n.a. -
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	11783-Part 10 Task Force
Submit Date	2005-03-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>142 - Physical Setpoint Time Latency</b>
Definition	The Setpoint Value Latency Time is the time lapse between the moment of receival of a setpoint value command by the working set and the moment this setpoint value is physically applied on the device. That means if the setpoint value is communicated on the network (CAN bus) but the system needs 2 seconds to adjust the value physically on the desired unit (device element) then the Setpoint Latency Time is 2 seconds. The setpoint time latency value can only be positive.
Comment	The use of this DDE is to inform the overall system (e.g. Dektop Software, Task Controller) how the system works. The TC shall not shift this information into log files nor shall the device do that when sending actual values.
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 14 - Special Crops
Unit Symbol	ms - Time
Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	11783-Part 10 Task Force
Submit Date	2005-03-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	2
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

<b>DD Entity</b>	<b>143 - Physical Actual Value Time Latency</b>
------------------	---

Definition	<p>The Actual Value Latency Time is the time lapse between the moment this actual value is communicated to the Task Controller, and the moment that this actual value is physically applied on the device. That means if the system needs 2 seconds to calculate or measure a value before communicating it on the network, then the Actual Latency Time value is minus 2 seconds.</p> <p>Depending of the system characteristics the latency time could be negative or positive.</p> <p>In case where the system communicates an actual value before the actual value has been physically applied the latency value should be positive.</p> <p>In case where the system communicates an actual value after the actual value has been physically applied the latency value should be negative.</p>
Comment	<p>The use of this DDE is to inform the overall system (e.g. Dektop Software, Task Controller) how the system works. The TC shall not shift this information into log files nor shall the device do that when sending actual values.</p> <p>Example for a positive value:</p> <p>A seed flow sensor is placed at the start of the seed tube. At the moment the sensor measures seed flow X, it takes Y seconds for this flow to reach the coulter. The measured value is ahead of the physical value of the unit (coulter). So the latency could be plus 2 seconds.</p> <p>Example for a negative value:</p> <p>A flow sensor has a delay in its response to a flow change that means it takes Y seconds to realize the change. At the moment the sensor measures flow X, the flow is already present for Y seconds on the physical unit. The actual value is ahead of measured value. So the latency could be minus 2 seconds.</p>
Typically used by Device Class(es)	<p>2 - Primary Soil Tillage  3 - Secondary Soil Tillage  4 - Planters /Seeders  5 - Fertilizer  6 - Sprayers  7 - Harvesters  8 - Root Harvester  9 - Forage harvester  10 - Irrigation  14 - Special Crops</p>
Unit Symbol	ms - Time

Resolution	1
SAE SPN	not specified
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	11783-Part 10 Task Force
Submit Date	2005-03-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	2
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	



<b>DD Entity</b>	<b>144 - Yaw Angle</b>
Definition	Pivot / Yaw Angle of a DeviceElement
Comment	This DDE was a result of March 2005 TF10 meeting
Typically used by Device Class(es)	
Unit Symbol	° - Angle
Resolution	0,001
SAE SPN	not specified
CANBus Range	-180000 - 180000
Display Range	-180,000 - 180,000
Submit by	11783-Part 10 Task Force
Submit Date	2005-03-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-05-09
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>145 - Roll Angle</b>
Definition	Roll Angle of a DeviceElement
Comment	This DDE was a result of March 2005 TF10 meeting
Typically used by Device Class(es)	
Unit Symbol	° - Angle
Resolution	0,001
SAE SPN	not specified
CANBus Range	-180000 - 180000
Display Range	-180,000 - 180,000
Submit by	11783-Part 10 Task Force
Submit Date	2005-03-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-05-09
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>146 - Pitch Angle</b>
Definition	Pitch Angle of a DeviceElement
Comment	This DDE was a result of March 2005 TF10 meeting
Typically used by Device Class(es)	
Unit Symbol	° - Angle
Resolution	0,001
SAE SPN	not specified
CANBus Range	-180000 - 180000
Display Range	-180,000 - 180,000
Submit by	11783-Part 10 Task Force
Submit Date	2005-03-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-05-09
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>147 - Log Count</b>
Definition	Log Counter, may be used to control data log record generation on a Task Controller
Comment	This DDE was a result of March 2005 TF10 meeting
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	n.a. -
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	11783-Part 10 Task Force
Submit Date	2005-03-01
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2005-05-09
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>148 - Total Fuel Consumption</b>
Definition	Accumulated Fuel Consumption as Counter
Comment	
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Stephan Zelleröhr
Submit Date	2005-04-12
Submit Company	103 - Agrocom GmbH & Co. Agrarsystem KG
Revision Number	1
Current Status	ISO-Published
Status Date	2005-05-09
Status Comments	DDEs have been moved to published for creating the new Annex A version.

<b>DD Entity</b>	<b>149 - Instantaneous Fuel Consumption per Time</b>
Definition	Fuel consumption per time
Comment	

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	mm <sup>3</sup> /s - Flow
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Stephan Zelleröhr
Submit Date	2005-04-12
Submit Company	103 - Agrocom GmbH & Co. Agrarsystem KG
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	Added "Instantaneous" for clarification

<b>DD Entity</b>	<b>150 - Instantaneous Fuel Consumption per Area</b>
Definition	Fuel consumption per area
Comment	
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	mm <sup>3</sup> /m <sup>2</sup> - Capacity per area unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Stephan Zelleröhr
Submit Date	2005-04-12
Submit Company	103 - Agrocom GmbH & Co. Agrarsystem KG
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	Added "Instantaneous" for clarification.

<b>DD Entity</b>	<b>151 - Instantaneous Area Per Time Capacity</b>
Definition	Area per time capacity
Comment	

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	mm <sup>2</sup> /s - Area per time unit
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Stephan Zelleröhr
Submit Date	2005-04-12
Submit Company	103 - Agrocom GmbH & Co. Agrarsystem KG
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	Added "Instantaneous" for clarification.

<b>DD Entity</b>	<b>153 - Actual Normalized Difference Vegetative Index (NDVI)</b>
Definition	The Normalized Difference Vegetative Index (NDVI) computed from crop reflectances as the difference between NIR reflectance in the 780 to 880 nm band and red reflectance in the 640 to 680 nm band divided by the sum of the NIR and red reflectance in the same bands.
Comment	Document attached.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	n.a. -
Resolution	0,001
SAE SPN	TBD
CANBus Range	-1 - 1
Display Range	-0,001 - 0,001
Submit by	Marvin Stone
Submit Date	2008-04-28
Submit Company	39 - Microfirm Inc.
Revision Number	1
Current Status	ISO-Approved
Status Date	0000-00-00
Status Comments	
Attachment	<a href="#">2009-08-11: Definition summary - NDVI definition summary.pdf</a>

<b>DD Entity</b>	<b>154 - Physical Object Length</b>
Definition	Length of device element (dimension along the X-axis)
Comment	The reference point of the device element shall be located in the center of the device element
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	mm - Length
Resolution	1
SAE SPN	

CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Hans Jürgen Nissen
Submit Date	2008-12-03
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	



<b>DD Entity</b>	<b>155 - Physical Object Width</b>
Definition	Width of device element (dimension along the Y-axis)
Comment	The reference point of the device element shall be located in the center of the device element
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxilary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Hans Jürgen Nissen
Submit Date	2008-12-03
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	

<b>DD Entity</b>	<b>156 - Physical Object Height</b>
Definition	Height of device element (dimension along the Z-axis)
Comment	The reference point of the device element shall be located in the center of the device element

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Hans Jürgen Nissen
Submit Date	2008-12-03
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	

DD Entity	157 - Connector Type
Definition	Specification of the type of coupler. The value definitions are: 0 = unknown (default), 1 = ISO 6489-3 Tractor drawbar, 2 = ISO 730 Three-point-hitch semi-mounted, 3 = ISO 730 Three-point-hitch mounted, 4 = ISO 6489-1 Hitch-hook, 5 = ISO 6489-2 Clevis coupling 40, 6 = ISO 6489-4 Piton type coupling, 7 = ISO 6489-5 CUNA hitch, or ISO 5692-2 Pivot wagon hitch 8 = ISO 24347 Ball type hitch all other values are reserved for future assignments.
Comment	This DDE allows systems to automatically select the connection between devices. For instance, when 2 devices are on the network that declare device elements with the same connector type, the system can connect them accordingly. This DDE shall be used with the Device Element of type "Connector" only.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 8
Display Range	0 - 8
Submit by	Hans Jürgen Nissen
Submit Date	2008-12-03
Submit Company	33 - John Deere
Revision Number	2
Current Status	ISO-Published
Status Date	2012-03-09
Status Comments	

DD Entity	158 - Prescription Control State
Definition	<p>Defines and synchronise the actual state of the prescription system. The state is represented by the lowest significant 2 bits in the lowest significant byte of the process data value: Byte 1: bit 0-1: 00 = manual/off, 01 = auto/on, 10 = error indicator, 11 = undefined/not installed. bits 2-7: reserved set to 0. Byte 2-4: reserved set to 0.</p> <p>The DDI shall support the On Change trigger so that the TC is able to get informed when the value gets changed by the Working Set Master. The TC shall active this trigger when using the DDI.</p> <p>See attachment for more information</p>
Comment	<p>The prescription control master and its clients need to be synchronized in terms of their general state or activation by the user (System activated/deactivated in individual setups). This DDE serves 2 purposes, one is to synchronize the prescription control state and the other is to enable a TC client to announce the support and initial state of its prescription control capabilities. Synchronisation by the prescription master (TC) is done by setting the prescription state of connected TC clients with a process data set value message with this DDE. It is recommended that TC clients reply their state immediately (within 250 ms) when such a message is received. The property flag "setable" and the trigger method "on change" shall be used with this DDE. The state "manual/off" indicates that the device is in manual state and will ignore all prescription commands. The "auto/on" state indicates that the client accepts the prescription commands as far as its overall process state allows.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3

Submit by	Matthias Meyer
Submit Date	2008-11-07
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	
Attachment	<a href="#">2010-04-06: Example Prescription Control State use - PCS Implementation Example.pdf</a>

<b>DD Entity</b>	<b>159 - Number of Sub-Units per Section</b>
Definition	Specifies the number of sub-units for a section (e.g. number of nozzles per sprayer section or number of planter row units per metering device).
Comment	This DDE is used for objects which have further sub-units per section, which are of interest to the operator but not needed for the Task Controller operation itself. With this information and the overall width of the section the system can calculate for instance the row spacing without having individual objects for each row in the DCD.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jason Walter
Submit Date	2008-12-03
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	

<b>DD Entity</b>	<b>160 - Section Control State</b>
------------------	------------------------------------

Definition	<p>Specifies the actual state of section control. The value definitions are: Byte 1 (bitfield) Bit 0-1: 00 = manual/off, 01 = auto/on, 10 = error indicator, 11 = undefined/not installed. Bits 2-7: reserved, set to 0. Bytes 2-4: reserved, set to 0.</p> <p>The DDI shall support the On Change trigger so that the TC is able to get informed when the value gets changed by the Working Set Master. The TC shall active this trigger when using the DDI.</p> <p>See attachment for more information</p>
------------	--

Comment	<p>In section control systems, the section control master and its clients need to be synchronized in terms of their general state or activation by the user (System activated/deactivated in individual setups). This DDE serves 2 purposes, one is to synchronize the section control state and the other is to enable a TC client to announce the support and initial state of its section control capabilities. Synchronisation by the section control master (TC) is done by setting the section control state of connected TC clients with a process data set value message with this DDE. It is recommended that TC clients reply their state immediately (within 250 ms) when such a message is received. The property flag "setable" and the trigger method "on change" should be used with this DDE. The state "manual/off" indicates that the device is in manual state and will ignore all control commands for section control. The "auto/on" state indicates that the client accepts the section control commands as far as its overall process state allows.</p> <p>Listed below are 4 example Use Cases for this DDE:</p> <p>Use case "Start up operation":</p> <ol style="list-style-type: none"> <li>1. During a start up the implement shall set the SCS to 'manual mode'.</li> </ol> <p>Use case "Auto request from TC":</p> <ol style="list-style-type: none"> <li>1. The implement receives an 'auto' request from TC.</li> <li>2. The implement shall check whether all setup conditions are fulfilled to allow section control.</li> <li>3. If this check is ok: The implement may respond with 'auto mode' and set its internal SCS client to 'auto mode'.</li> <li>4. If this check not ok: The implement shall respond with 'manual mode'. The internal state is still in manual mode. The TC may inform the operator accordingly.</li> </ol> <p>Use case "Manual request from TC":</p> <ol style="list-style-type: none"> <li>1. The implement receives a manual request from TC.</li> <li>2. If the implement is still in 'auto mode' the implement shall set its internal SCS client to 'manual mode'.</li> </ol> <p>Use case "Loss of requirements for auto mode":</p> <ol style="list-style-type: none"> <li>1. The implement internal setup conditions don't allow for automatic section control anymore.</li> <li>2. The implement shall set the internal SCS client to 'manual mode'.</li> <li>3. The implement shall send the SCS to inform the TC accordingly.</li> </ol> <p>On reception of this 'manual mode' the TC/Section Control Master may inform the operator accordingly.</p>
Typically used by Device Class(es)	<p>0 - Non-specific system</p> <p>4 - Planters /Seeders</p> <p>5 - Fertilizer</p> <p>6 - Sprayers</p>



Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	Matthias Meyer
Submit Date	2008-12-03
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	

<b>DD Entity</b>	<b>161 - Actual Condensed Work State (1-16)</b>
Definition	Combination of the actual work states of individual sections or units (e.g. nozzles) number 1 to 16 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.
Comment	See attachment on DDI 290 "ISO11783-11-DDI-290-SetpointCondensedWorkState" for implementation guideline.  This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxilary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief

Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>162 - Actual Condensed Work State (17-32)</b>
Definition	<p>Combination of the actual work states of individual sections or units (e.g. nozzles) number 17 to 32 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.</p>
Comment	<p>See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.</p> <p>This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief
Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>163 - Actual Condensed Work State (33-48)</b>
Definition	Combination of the actual work states of individual sections or units (e.g. nozzles) number 33 to 48 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.
Comment	See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.  This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxilary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief

Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>164 - Actual Condensed Work State (49-64)</b>
Definition	<p>Combination of the actual work states of individual sections or units (e.g. nozzles) number 49 to 64 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.</p>
Comment	<p>See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.</p> <p>This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief
Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>165 - Actual Condensed Work State (65-80)</b>
Definition	Combination of the actual work states of individual sections or units (e.g. nozzles) number 65 to 80 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.
Comment	See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.  This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxilary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief



Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>166 - Actual Condensed Work State (81-96)</b>
Definition	<p>Combination of the actual work states of individual sections or units (e.g. nozzles) number 81 to 96 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.</p>
Comment	<p>See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.</p> <p>This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief
Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>167 - Actual Condensed Work State (97-112)</b>
Definition	Combination of the actual work states of individual sections or units (e.g. nozzles) number 97 to 112 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.
Comment	See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.  This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxilary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief

Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>168 - Actual Condensed Work State (113-128)</b>
Definition	<p>Combination of the actual work states of individual sections or units (e.g. nozzles) number 113 to 128 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.</p>
Comment	<p>See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.</p> <p>This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief
Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>169 - Actual Condensed Work State (129-144)</b>
Definition	Combination of the actual work states of individual sections or units (e.g. nozzles) number 129 to 144 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.
Comment	See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.  This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief

Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>170 - Actual Condensed Work State (145-160)</b>
Definition	<p>Combination of the actual work states of individual sections or units (e.g. nozzles) number 145 to 160 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.</p>
Comment	<p>See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.</p> <p>This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief
Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	



<b>DD Entity</b>	<b>171 - Actual Condensed Work State (161-176)</b>
Definition	Combination of the actual work states of individual sections or units (e.g. nozzles) number 161 to 176 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.
Comment	See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.  This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief

Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>172 - Actual Condensed Work State (177-192)</b>
Definition	<p>Combination of the actual work states of individual sections or units (e.g. nozzles) number 177 to 192 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.</p>
Comment	<p>See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.</p> <p>This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief
Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>173 - Actual Condensed Work State (193-208)</b>
Definition	Combination of the actual work states of individual sections or units (e.g. nozzles) number 193 to 208 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.
Comment	See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.  This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxilary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief

Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>174 - Actual Condensed Work State (209-224)</b>
Definition	<p>Combination of the actual work states of individual sections or units (e.g. nozzles) number 209 to 224 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.</p>
Comment	<p>See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.</p> <p>This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief
Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>175 - Actual Condensed Work State (225-240)</b>
Definition	Combination of the actual work states of individual sections or units (e.g. nozzles) number 225 to 240 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.
Comment	See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.  This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief

Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>176 - Actual Condensed Work State (241-256)</b>
Definition	<p>Combination of the actual work states of individual sections or units (e.g. nozzles) number 241 to 256 into a single actual work state of their parent device element. The actual condensed work state contains the child element actual work states, in the driving direction from left to right, where the leftmost child element actual work state are the 2 lowest significant bits of the Process Data Value. Each child device elements actual work state is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element actual work states can be contained in one actual condensed work state of their parent device element. If less than 16 child device element actual work states are available, then the unused bits shall be set to value 11 (not installed). When the parent device element contains the Actual Condensed Work State DDE, then the device descriptor shall not contain the individual actual work state DDEs of the child device elements.</p>
Comment	<p>See the DDI 161 attachment "ISO11783-11-DDI-289-SetpointWorkState" for implementation guidelines.</p> <p>This DDE is used to reduce number of messages. Individual work state messages for a many-sectioned device can potentially cause performance issues due to overloading communication. With this DDE, 16 work states can be sent via a single message, resulting in less traffic to convey on/off status for an entire device.</p>



Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Adam Bogenrief
Submit Date	2008-01-14
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>177 - Actual length of cut</b>
Definition	Actual length of cut for harvested material, e.g. Forage Harvester or Tree Harvester.
Comment	none.
Typically used by Device Class(es)	0 - Non-specific system 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483,647
Display Range	0,000 - 2,147,484
Submit by	Hans Jürgen Nissen
Submit Date	2008-09-22
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	

<b>DD Entity</b>	<b>178 - Element Type Instance</b>
Definition	This DDI is used to enumerate and identify multiple device elements (DET) of the same type within one Device Description object pool. The value of this DDI is independent of the DET number. The combination of device element type and value of Element Type Instance ETI represents a unique object inside the device description object pool and therefore shall exist only once per object pool. Recommendation: The definition of the device elements should be made from left to right direction or from front to back direction. When in a matrix, count left-to-right first, then front-to-back and at last top-to-bottom. See attachment for more information.
Comment	This DDE allows the system to communicate with a device element object independent of the device element number. The same tank of a seeder for instance could have various device element numbers based upon the DDD. The DDD structure may change during setup the implement. In this case a unique implement tank might has a different element number as before. Particular if the Task Controller (TC) use a user interface to display and change data by the operator. Therefore the TC needs clear or rather unique device element information. Assign this DDE for instance to a DET of type bin. This number can be displayed to the operator while it may be printed physically at the bin. The ETI number range from 0 to 65533 inside the object pool corresponds to a displayed value from 1 to 65534 on a user interface or physical device.

Typically used by Device Class(es)	- Not Assigned
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 65533
Display Range	0 - 65533
Submit by	Matthias Meyer
Submit Date	2010-01-15
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	
Attachment	<a href="#">2010-04-06: Example Device Descriptions with Element Type Instance DDI - Mixed product implement DDD recommendation 20100118.pdf</a>

<b>DD Entity</b>	<b>179 - Actual Cultural Practice</b>
Definition	<p>This DDI is used to define the current cultural practice which is performed by an individual device operation. For instance a planter/seeder could provide a sowing and a fertilizing operation at the same time.</p> <p>The cultural practice value definitions are: 0=Unknown, 1=Fertilizing, 2=Sowing and Planting, 3=Crop Protection, 4=Tillage, 5=Baling, 6=Mowing, 7=Wrapping, 8=Harvesting, 9=Forage Harvesting, 10=Transport, 11=Swathing, 12=Slurry/Manure Application, 13-255=Reserved for future Assignment</p> <p>See attachment for more information.</p>
Comment	<p>Implements as Planter or Seeder which provides more than one product application need an option to sign the cultural practice that is performed by each operation. More then ever if the applied products have the same unit type. As for instance a seeder provides a sowing and fertilizing operation which have both mass per area as unit defined. In this case it is not clear to the TC that the second operation is a fertilizing operation. Particular if the TC owns a user interface to display these information to the operator. Through this DDE the TC user interface can display the appropriate information. Adding this DDI to the device element of type device the main cultural practice of the device could be defined. For instance a baler will claim on the bus as forage device class and have set the actual cultural practice as baling.</p>
Typically used by Device Class(es)	<p>0 - Non-specific system  1 - Tractor  2 - Primary Soil Tillage  3 - Secondary Soil Tillage  4 - Planters /Seeders  5 - Fertilizer  6 - Sprayers  7 - Harvesters  8 - Root Harvester  9 - Forage harvester  10 - Irrigation  11 - Transport / Trailers  12 - Farmyard Work  13 - Powered Auxilary Units  14 - Special Crops</p>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2010-01-15

Submit Company	33 - John Deere
Revision Number	2
Current Status	ISO-Published
Status Date	2015-01-28
Status Comments	
Attachment	<a href="#">2011-01-11: - Multiple and Single Product Implement Description.pdf</a>

<b>DD Entity</b>	<b>180 - Device Reference Point (DRP) to Ground distance</b>
Definition	This DDI is used to specify the distance from the Device Reference Point (DRP) down to the ground surface. The DRP to Ground DDI shall be attached only to the Device Element (DET) with element number zero.
Comment	Depending on the application it might be required to know the distance of a device element down to the ground. All device element offsets refer to the DRP which is the centre of the device coordinate system and usually not at the ground surface. For instance the DRP of a tractor is the centre of the rear axle. In this case the distance from a GPS receiver (DET of type navigation reference) attached on the roof of the cab is calculated through sum up the Z-offset of the DET and the distance of the DRP to ground. The value of the DRP in this case is equivalent to the radius of the rolling wheel which is attached on the tractor rear axle.
Typically used by Device Class(es)	
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2010-01-15
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>181 - Dry Mass Per Area Yield</b>
Definition	Actual Dry Mass Per Area Yield. The definition of dry mass is the mass with a reference moisture specified by DDI 184.
Comment	The earlier defined DDI 84 is the mass per area that is measured on e.g. harvesting equipment as a mass including a possibly unknown moisture percentage. This DDI 181 is the mass per area yield, corrected to a reference moisture.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Lyle Jensen
Submit Date	2010-01-29
Submit Company	102 - AGCO GmbH & Co
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>182 - Dry Mass Per Time Yield</b>
Definition	Actual Dry Mass Per Time Yield. The definition of dry mass is the mass with a reference moisture specified by DDI 184.
Comment	The earlier defined DDI 87 is the mass per time that is measured on e.g. harvesting equipment as a mass including a possibly unknown moisture percentage. This DDI 182 is the mass per time yield, corrected to a reference moisture.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Lyle Jensen
Submit Date	2010-01-29
Submit Company	102 - AGCO GmbH & Co
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>183 - Yield Total Dry Mass</b>
Definition	Accumulated Yield specified as dry mass. The definition of dry mass is the mass with a reference moisture specified by DDI 184.
Comment	The earlier defined DDI 90 is considered to be the total mass that is measured on e.g. harvesting equipment as a mass including a possibly unknown moisture percentage. This DDI 183 is the yield total mass, corrected to a reference moisture.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Lyle Jensen
Submit Date	2010-01-29
Submit Company	102 - AGCO GmbH & Co
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>184 - Reference Moisture For Dry Mass</b>
Definition	Moisture percentage used for the dry mass DDIs 181, 182 and 183.
Comment	Example: this definition is similar to the "Standard Payable Moisture" term used by farmers.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Lyle Jensen
Submit Date	2010-01-29
Submit Company	102 - AGCO GmbH & Co
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>185 - Seed Cotton Mass Per Area Yield</b>
Definition	Seed cotton yield as mass per area, not corrected for a possibly included lint percentage.
Comment	This Seed Cotton Mass Per Area Yield is the mass of the raw harvested cotton product as it is measured on e.g. harvesting equipment.
Typically used by Device Class(es)	7 - Harvesters 14 - Special Crops
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Andy Beck
Submit Date	2010-02-26
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>186 - Lint Cotton Mass Per Area Yield</b>
Definition	Lint cotton yield as mass per area.
Comment	This Lint Cotton Mass Per Area Yield is the mass of the lint after it has been removed from the seed cotton at a cotton gin. Calculated by use of the Lint Turnout Percentage.
Typically used by Device Class(es)	7 - Harvesters 14 - Special Crops
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Andy Beck
Submit Date	2010-02-26
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	



<b>DD Entity</b>	<b>187 - Seed Cotton Mass Per Time Yield</b>
Definition	Seed cotton yield as mass per time, not corrected for a possibly included lint percentage.
Comment	This Seed Cotton Mass Per Time Yield is the mass of the raw harvested cotton product as it is measured on e.g. harvesting equipment.
Typically used by Device Class(es)	7 - Harvesters 14 - Special Crops
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Andy Beck
Submit Date	2010-02-26
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>188 - Lint Cotton Mass Per Time Yield</b>
Definition	Lint cotton yield as mass per time.
Comment	This Lint Cotton Mass Per Time Yield is the mass of the lint after it has been removed from the seed cotton at a cotton gin. Calculated by use of the Lint Turnout Percentage.
Typically used by Device Class(es)	7 - Harvesters 14 - Special Crops
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Andy Beck
Submit Date	2010-02-26
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>189 - Yield Total Seed Cotton Mass</b>
Definition	Accumulated yield specified as seed cotton mass, not corrected for a possibly included lint percentage.
Comment	This Yield Total Seed Cotton Mass is the total mass of the raw harvested cotton product as it is measured on e.g. harvesting equipment.
Typically used by Device Class(es)	7 - Harvesters 14 - Special Crops
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Andy Beck
Submit Date	2010-02-26
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>190 - Yield Total Lint Cotton Mass</b>
Definition	Accumulated yield specified as lint cotton mass.
Comment	This Yield Total Lint Cotton Mass is the total lint cotton mass, after it has been removed from the total seed cotton at a cotton gin.
Typically used by Device Class(es)	7 - Harvesters 14 - Special Crops
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Andy Beck
Submit Date	2010-02-26
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>191 - Lint Turnout Percentage</b>
Definition	Percent of lint in the seed cotton.
Comment	
Typically used by Device	7 - Harvesters
Class(es)	14 - Special Crops
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Andy Beck
Submit Date	2010-02-26
Submit Company	33 - John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2010-03-12
Status Comments	

<b>DD Entity</b>	<b>192 - Ambient temperature</b>
Definition	Ambient temperature measured by a machine. Unit is milli-Kelvin (mK).
Comment	
Typically used by Device	0 - Non-specific system
Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	mK - Temperature
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Timo Oksanen
Submit Date	2011-01-17
Submit Company	Aalto University
Revision Number	1

Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

<b>DD Entity</b>	<b>193 - Setpoint Product Pressure</b>
Definition	Setpoint Product Pressure to adjust the pressure of the product flow system at the point of dispensing.
Comment	On pressure-based control systems, it is important to be able to monitor and control the system pressure to ensure the proper flow rate and droplet size. Being able to display and log pressure is important. On sprayers, this would be the boom pressure.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-01-19
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-03-27
Status Comments	

<b>DD Entity</b>	<b>194 - Actual Product Pressure</b>
Definition	Actual Product Pressure is the measured pressure in the product flow system at the point of dispensing.
Comment	On pressure-based control systems, it is important to be able to monitor and control the system pressure to ensure the proper flow rate and droplet size. Being able to display and log pressure is important. On sprayers, this would be the boom pressure.

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-03-09
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

<b>DD Entity</b>	<b>195 - Minimum Product Pressure</b>
Definition	Minimum Product Pressure in the product flow system at the point of dispensing.
Comment	Minimum system product pressure to ensure a consistent product flow. See also "Setpoint Product Pressure"
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-03-09
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

<b>DD Entity</b>	<b>196 - Maximum Product Pressure</b>
Definition	Maximum Product Pressure in the product flow system at the point of dispensing.
Comment	Maximum system product to ensure a stable and safe product flow. See also "Setpoint Product Pressure"

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-03-09
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	



<b>DD Entity</b>	<b>197 - Setpoint Pump Output Pressure</b>
Definition	Setpoint Pump Output Pressure to adjust the pressure at the output of the solution pump.
Comment	
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-01-19
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-03-27
Status Comments	

<b>DD Entity</b>	<b>198 - Actual Pump Output Pressure</b>
Definition	Actual Pump Output Pressure measured at the output of the solution pump.
Comment	

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-03-09
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

<b>DD Entity</b>	<b>199 - Minimum Pump Output Pressure</b>
Definition	Minimum Pump Output Pressure for the output pressure of the solution pump.
Comment	
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxilary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-03-09
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

<b>DD Entity</b>	<b>200 - Maximum Pump Output Pressure</b>
Definition	Maximum Pump Output Pressure for the output pressure of the solution pump.
Comment	

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-03-09
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

<b>DD Entity</b>	<b>201 - Setpoint Tank Agitation Pressure</b>
Definition	Setpoint Tank Agitation Pressure to adjust the pressure for a stir system in a tank.
Comment	In a liquid application system, this is the pressure used to stir the tank contents to prevent products in liquid suspension from settling in the tank.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-01-19
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-03-27
Status Comments	

<b>DD Entity</b>	<b>202 - Actual Tank Agitation Pressure</b>
Definition	Actual Tank Agitation Pressure measured by the tank stir system.
Comment	In a liquid application system, this is the pressure used to stir the tank contents to prevent products in liquid suspension from settling in the tank. Typically measured at the agitation manifold.

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-03-09
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

<b>DD Entity</b>	<b>203 - Minimum Tank Agitation Pressure</b>
Definition	Minimum Tank Agitation Pressure for a stir system in a tank.
Comment	Minimum tank agitation pressure to prevent products in liquid suspension from settling in the tank. See also "Setpoint Tank Agitation Pressure".
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-03-09
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

<b>DD Entity</b>	<b>204 - Maximum Tank Agitation Pressure</b>
Definition	Maximum Tank Agitation Pressure for a stir system in a tank.
Comment	Maximum tank agitation pressure to prevent products in liquid suspension from settling in the tank. See also "Setpoint Tank Agitation Pressure"

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748364,8 - 214748364,7
Submit by	Tony Woodcock
Submit Date	2011-03-09
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-05
Status Comments	



<b>DD Entity</b>	<b>205 - SC Turn On Time</b>
Definition	<p>The Section Control Turn On Time defines the overall time lapse between the moment the TC sends a turn on section command to the working set and the moment this section is physically turned on and the product is applied.</p> <p>The working set may support this DDE as an optional feature to provide the possibility to store the time settings direct on the device to make the settings available after a power cycle. Therefore this DDE needs always to be settable by the TC and shall not be used to change any working set system behavior.</p> <p>The DDI shall support the On Change trigger so that the TC is able to get informed when the value gets changed by the Working Set Master. The TC shall active this trigger when using the DDI.</p>
Comment	<p>The SC Turn On Time setting is used to compensate the average physical machine reaction time (Electrical &amp; Mechanical) from the moment the Task Controller send the command and the Working Set applies the product.</p> <p>To find the right time setting for the used system combination of Task Controller and Working Set it could take awhile and therefore it is a big benefit to store the setting on the working set to make them again available after a power cycle. For working sets supporting Section Control it is recommended to add SC Turn On Time to its device description and make it settable.</p> <p>In case where the device description contains also Physical Setpoint Time Latency or Physical Actual Time Latency the TC Turn On Time will always supercede it.</p>
Typically used by Device Class(es)	<p>0 - Non-specific system</p> <p>4 - Planters /Seeders</p> <p>5 - Fertilizer</p> <p>6 - Sprayers</p>
Unit Symbol	ms - Time
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2011-03-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-03-28
Status Comments	

<b>DD Entity</b>	<b>206 - SC Turn Off Time</b>
------------------	-------------------------------

Definition	<p>The Section Control Turn Off Time defines the overall time lapse between the moment the TC sends a turn off section command to the working set and the moment this section is physically turned off.</p> <p>The working set may support this DDE as an optional feature to provide the possibility to store the time settings direct on the device to make the settings available after a power cycle. Therefore this DDE needs always to be settable by the TC and shall not be used to change any working set system behavior.</p> <p>The DDI shall support the On Change trigger so that the TC is able to get informed when the value gets changed by the Working Set Master. The TC shall active this trigger when using the DDI.</p>
Comment	<p>The SC Turn Off Time setting is used to compensate the average physical machine reaction time (Electrical &amp; Mechanical) from the moment the Task Controller send the command and the Working Set turns off the sections.</p> <p>To find the right time setting for the used system combination of Task Controller and Working Set it could take awhile and therefore it is a big benefit to store the setting on the Working Set to make them again available after a power cycle. For Working Sets supporting Section Control it is recommended to add SC Turn Off Time to its device description and make it settable.</p>
Typically used by Device Class(es)	<p>0 - Non-specific system</p> <p>4 - Planters /Seeders</p> <p>5 - Fertilizer</p> <p>6 - Sprayers</p>
Unit Symbol	ms - Time
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2011-03-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-03-28
Status Comments	

<b>DD Entity</b>	<b>207 - Wind speed</b>
Definition	Wind speed measured in the treated field at the beginning of operations or on the application implement during operations. Measurements at to be made at 2m height or 1 m over the canopy in tree and bush crops. On implements the wind speed needs to be compansated by implement true ground speed and heading.
Comment	Requested by TC23 SC6 WG15
Typically used by Device Class(es)	1 - Tractor 5 - Fertilizer 6 - Sprayers 10 - Irrigation 14 - Special Crops 17 - Sensor System
Unit Symbol	mm/s - Speed
Resolution	1
SAE SPN	
CANBus Range	0 - 100000000
Display Range	0 - 100000000
Submit by	Bob Benneweis
Submit Date	2011-03-16
Submit Company	Benneweis Consulting Ltd
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

<b>DD Entity</b>	<b>208 - Wind direction</b>
Definition	Wind direction measured in the treated field at the beginning of operations or on the application implement during operations. Measurements at to be made at 2m height or 1 m over the canopy in tree and bush crops. On implements the wind direction needs to be compansated by implement true ground speed and heading.
Comment	
Typically used by Device Class(es)	1 - Tractor 5 - Fertilizer 6 - Sprayers 10 - Irrigation 14 - Special Crops 17 - Sensor System
Unit Symbol	° - Angle
Resolution	1
SAE SPN	
CANBus Range	0 - 359
Display Range	0 - 359
Submit by	Bob Benneweis

Submit Date	2011-03-16
Submit Company	Benneweis Consulting Ltd
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

DD Entity	209 - Air Humidity
Definition	Ambient humidity measured by a weather station in a treated field or on the application implement.
Comment	
Typically used by Device Class(es)	1 - Tractor 5 - Fertilizer 6 - Sprayers 7 - Harvesters 9 - Forage harvester 10 - Irrigation 14 - Special Crops 17 - Sensor System
Unit Symbol	% - Percent
Resolution	1
SAE SPN	
CANBus Range	0 - 100
Display Range	0 - 100
Submit by	Bob Benneweis
Submit Date	2011-03-16
Submit Company	Benneweis Consulting Ltd
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-04
Status Comments	

DD Entity	210 - Sky conditions
Definition	<p>This DDE is used to define the current sky conditions during operation. The METAR format and its abbreviations is used as follows to define the sky conditions:</p> <p>CLR=Clear, NSC=Mostly Sunny, FEW=Partly Sunny, SCT=Partly cloud, BKN=Mostly cloudy, OVC=overcast/cloudy</p> <p>1. Byte = first character 2. Byte = second character 3. Byte = third character 4. Byte = fourth character</p> <p>Unused bytes shall be set to 0x20 Byte 1 to 4 set to 0x00 = error Byte 1 to 4 set to 0xFF = not available</p>

Comment	To setup the METAR abbreviations the ISO 8859-1 standard is used. From the Latin-1 printable characters set the capitals from "A" (0x41) to "Z" (0x5A ) shall be used. The space "SP" (0x20) is used for unused bytes.  Example for Clear (CLR): 1. Byte = 0x43(C) 2. Byte = 0x4C(L) 3. Byte = 0x52 (R) 4. Byte = 0x20 (unused)
Typically used by Device Class(es)	1 - Tractor 5 - Fertilizer 6 - Sprayers 7 - Harvesters 9 - Forage harvester 10 - Irrigation 14 - Special Crops 17 - Sensor System
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Bob Benneweis
Submit Date	2011-03-16
Submit Company	Benneweis Consulting Ltd
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-29
Status Comments	

<b>DD Entity</b>	<b>211 - Last Bale Flakes per Bale</b>
Definition	The number of flakes in the most recently produced bale.
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler can add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 1000
Display Range	0 - 1000
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>212 - Last Bale Average Moisture</b>
Definition	The average moisture in the most recently produced bale.
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler may add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 100000000
Display Range	0 - 100000000
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>213 - Last Bale Average Strokes per Flake</b>
Definition	The number of baler plunger compression strokes per flake that has entered the bale compression chamber. This value is the average valid for the most recently produced bale.
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler may add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 1000
Display Range	0 - 1000
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>214 - Lifetime Bale Count</b>
Definition	The number of bales produced by a machine over its entire lifetime. This DDE value can not be set through the process data interface but can be requested and added to a datalog. This DDE value is not affected by a task based total bales but will increment at the same rate as the task based total.
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler may add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1



Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>215 - Lifetime Working Hours</b>
Definition	The number of working hours of a device element over its entire lifetime. This DDE value can not be set through the process data interface but can be requested and added to a datalog.
Comment	<p>The recommended use of this DDE is to be transmitted on a request basis only.</p> <p>The Lifetime Working Hours is the overall time when the device was turned on.</p> <p>This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be settable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the settable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p> <p>Note: unit is h and the bit resolution is 0.05 h/bit, this aligns the resolution and range with similar SPNs as defined in SAE J1939-71.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> </ul>
Unit Symbol	h - Hour
Resolution	0,05
SAE SPN	
CANBus Range	0 - 210554060,75
Display Range	0,0 - 10527703,038
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30

Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>216 - Actual Bale Hydraulic Pressure</b>
Definition	The actual value of the hydraulic pressure applied to the sides of the bale in the bale compression chamber.
Comment	The actual pressure is the resultant of the baler controller targeting a certain setpoint plunger load.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	Pa - Pressure
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>217 - Last Bale Average Hydraulic Pressure</b>
Definition	The average actual value of the hydraulic pressure applied to the sides of the bale in the bale compression chamber. This average is calculated over the most recently produced bale.
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler may add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	Pa - Pressure
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>218 - Setpoint Bale Compression Plunger Load</b>
Definition	The setpoint bale compression plunger load as a unitless number.
Comment	This value is measured / controlled for each new flake that entered the baler chamber and obtained at the rear dead end of the plunger.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 2000
Display Range	0 - 2000
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>219 - Actual Bale Compression Plunger Load</b>
Definition	The actual bale compression plunger load as a unitless number.
Comment	This is the plunger load measured at the rear dead end of the plunger cycle and only updated for each new flake that has entered the baler chamber.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 2000
Display Range	0 - 2000
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>220 - Last Bale Average Bale Compression Plunger Load</b>
Definition	The average bale compression plunger load for the most recently produced bale.
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler may add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 2000
Display Range	0 - 2000
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>221 - Last Bale Applied Preservative</b>
Definition	The total preservative applied to the most recently produced bale.
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler may add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>222 - Last Bale Tag Number</b>
Definition	The Last Bale Tag Number as a decimal number in the range of 0 to 4294967295. Note that the value of this DDI has the limitation of being an unsigned 32 bit number.
Comment	For balers: the recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler may add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved

Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>223 - Last Bale Mass</b>
Definition	The mass of the bale that has most recently been produced.
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler may add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-04-30
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-04-30
Status Comments	

<b>DD Entity</b>	<b>224 - Delta T</b>
Definition	The difference between dry bulb temperature and wet bulb temperature measured by a weather station in a treated field or on the application equipment.
Comment	This parameter is used to determine spray effectiveness in hot and dry environments. If the Delta T value is too high the effectiveness of the overall spray application does not match the requirement for this operation. This value can be used by the application to notify the operator about the effectiveness and whether he should continue with the application or not. It can also be used to document the application environment within the log files for the task.
Typically used by Device Class(es)	5 - Fertilizer 6 - Sprayers 7 - Harvesters 9 - Forage harvester 17 - Sensor System
Unit Symbol	mK - Temperature
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Matthias Meyer
Submit Date	2011-05-25



Submit Company	John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2011-06-20
Status Comments	

<b>DD Entity</b>	<b>225 - Setpoint Working Length</b>
Definition	Setpoint Working Length of Device Element.
Comment	This is the desired working length of the device element during operation. For the geometry definition and example use, see the attachment of the Actual Working Length, DDI 226.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxillary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Moritz Roeingh
Submit Date	2011-07-12
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2011-08-31
Status Comments	

<b>DD Entity</b>	<b>226 - Actual Working Length</b>
Definition	Actual Working Length of a Device Element.
Comment	Used for Section Control. By using the Actual Working Length of a device element a rectangular area is defined. This area represents the current working area and defines offsets for turning sections on and off by Section Control. The Actual Working Length parameter is useful for fertilizer spreaders and similar implements.

Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Moritz Roeingh
Submit Date	2011-07-07
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2011-08-31
Status Comments	
Attachment	<a href="#">2012-07-03: - ISO11783-11-DDI-226-ActualWorkingLength-v1.pdf</a>

<b>DD Entity</b>	<b>227 - Minimum Working Length</b>
Definition	Minimum Working Length of Device Element.
Comment	This is the minimum working length of the device element during operation. For the geometry definition and example use, see the attachment of the Actual Working Length, DDI 226.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxillary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Moritz Roeingh
Submit Date	2011-07-12
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2011-08-31
Status Comments	

<b>DD Entity</b>	<b>228 - Maximum Working Length</b>
Definition	Maximum Working Length of Device Element.
Comment	This is the maximum working length of the device element during operation. For the geometry definition and example use, see the attachment of the Actual Working Length, DDI 226.

Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Moritz Roeingh
Submit Date	2011-07-12
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2011-08-31
Status Comments	

<b>DD Entity</b>	<b>229 - Actual Net Weight</b>
Definition	Actual Net Weight value specified as mass
Comment	The Actual Net Weight is the current measured mass by a weighing system. For more information see attachment located at Actual Net Weight DDE
Typically used by Device Class(es)	11 - Transport / Trailers 17 - Sensor System
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2011-09-13
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2011-09-28
Status Comments	
Attachment	<a href="#">2011-09-28: - ISO11783-11-DDI-229-Weighing System Implementation.pdf</a>

<b>DD Entity</b>	<b>230 - Net Weight State</b>
Definition	Net Weight State, 2 bits defined as: 00 = unstable measurement 01 = stable measurement 10 = error (measuring error)
Comment	The Net Weight State indicates whether the current Actual Net Weight value is a reliable value or not. Example: After a mass of grain is filled into a grain cart it takes a while until the weighing system is able to provide the valid value of the load.
Typically used by Device Class(es)	11 - Transport / Trailers 17 - Sensor System
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	Matthias Meyer
Submit Date	2011-09-13
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2011-09-28
Status Comments	

<b>DD Entity</b>	<b>231 - Setpoint Net Weight</b>
Definition	Setpoint Net Weight value.
Comment	The Setpoint Net Weight value is used to prompt the weighing system to perform a tare procedure. For more information see attachment located at Actual Net Weight DDE.
Typically used by Device Class(es)	11 - Transport / Trailers 17 - Sensor System
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2011-09-13
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2011-09-28
Status Comments	

<b>DD Entity</b>	<b>232 - Actual Gross Weight</b>
Definition	Actual Gross Weight value specified as mass
Comment	The Actual Gross Weight is the overall measured mass by a weighing system. For more information see attachment located at Actual Net Weight DDE.
Typically used by Device Class(es)	11 - Transport / Trailers 17 - Sensor System
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2011-09-13
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2011-09-28
Status Comments	

<b>DD Entity</b>	<b>233 - Gross Weight State</b>
Definition	Gross Weight State, 2 bits defined as: 00 = unstable measurement 01 = stable measurement 10 = error (measuring error)
Comment	The Gross Weight State indicates whether the current Actual Gross Weight value is a reliable value or not. For more information see attachment located at Actual Net Weight DDE.  Example: After a mass of grain is filled into a grain cart it takes a while until the weighing system is able to provide the valid value of the load.
Typically used by Device Class(es)	11 - Transport / Trailers 17 - Sensor System
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	Matthias Meyer
Submit Date	2011-09-13
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2011-09-28
Status Comments	

<b>DD Entity</b>	<b>234 - Minimum Gross Weight</b>
Definition	Minimum Gross Weight specified as mass.
Comment	The Minimum Gross Weight may represent the minimum value of the effective range of the weighing system. For more information see attachment located at Actual Net Weight DDE.
Typically used by Device Class(es)	11 - Transport / Trailers 17 - Sensor System
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2011-09-13
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2011-09-28
Status Comments	



<b>DD Entity</b>	<b>235 - Maximum Gross Weight</b>
Definition	Maximum Gross Weight specified as mass.
Comment	Maximum Gross Weight may represent the maximum value of the effective range of the weighing system. For more information see attachment located at Actual Net Weight DDE.
Typically used by Device Class(es)	11 - Transport / Trailers 17 - Sensor System
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2011-09-13
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2011-09-28
Status Comments	

<b>DD Entity</b>	<b>236 - Thresher Engagement Total Time</b>
Definition	Accumulated time while the threshing mechanism is engaged
Comment	This DDE represents the total engagement time of the threshing mechanism of the machine and is recommended to be used at maximum once within the device description in the device element that represents the machine.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	s - Time count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>237 - Actual Header Working Height Status</b>
Definition	Actual status of the header being above or below the threshold height for the in-work state. 2 bit status indicator: 00=disabled/off/above threshold height 01=enabled/on/below threshold height 10=error 11=undefined/not installed
Comment	The DDE has been defined to be able to communicate a more detailed work state of a machine.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-11-17
Status Comments	

<b>DD Entity</b>	<b>238 - Actual Header Rotational Speed Status</b>
Definition	Actual status of the header rotational speed being above or below the threshold for in-work state. 2 bit status indicator: 00=disabled/off/below threshold speed 01=enabled/on/above threshold speed 10=error 11=undefined/not installed
Comment	The DDE has been defined to be able to communicate a more detailed work state of a machine.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	Robert Waggoner

Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>239 - Yield Hold Status</b>
Definition	Status indicator for the yield measurement system. When enabled/on, the measurements from the yield measurement system are ignored and the yield is held constant. 2 bit status indicator: 00=disabled/off 01=enabled/on 10=error 11=undefined/not installed
Comment	This status indicator can e.g. be set by the operator when entering an area of the field where the yield measurement system yield measurements should not be used. This DDE shall not be settable by the TC. The values of the following list of DDE's is are held constant when this DDE is enabled/on: DDI's 83 to 91, 181 to 183 and 185 to 190.
Typically used by Device Class(es)	6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>240 - Actual (Un)Loading System Status</b>
------------------	---

Definition	Actual status of the Unloading and/or Loading system. This DDE covers both Unloading and Loading of the device element wherein it is listed. Byte 1: 2 bit unloading status indicator: 00=disabled/off 01=enabled/on/unloading 10=error 11=undefined/not installed Byte 2: 2 bit loading status indicator: 00=disabled/off 01=enabled/on/loading 10=error 11=undefined/not installed
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>241 - Crop Temperature</b>
Definition	Temperature of harvested crop
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mK - Temperature
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>242 - Setpoint Sieve Clearance</b>
Definition	Setpoint separation distance between Sieve elements
Comment	
Typically used by Device Class(es)	6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>243 - Actual Sieve Clearance</b>
Definition	Actual separation distance between Sieve elements
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>244 - Minimum Sieve Clearance</b>
Definition	Minimal separation distance between Sieve elements
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>245 - Maximum Sieve Clearance</b>
Definition	Maximum separation distance between Sieve elements.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-10-17
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>246 - Setpoint Chaffer Clearance</b>
Definition	Setpoint separation distance between Chaffer elements.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-10-17
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	



DD Entity	247 - Actual Chaffer Clearance
Definition	Actual separation distance between Chaffer elements.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	3
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

DD Entity	248 - Minimum Chaffer Clearance
Definition	Minimum separation distance between Chaffer elements.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-10-17
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>249 - Maximum Chaffer Clearance</b>
Definition	Maximum separation distance between Chaffer elements.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-10-17
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>250 - Setpoint Concave Clearance</b>
Definition	Setpoint separation distance between Concave elements.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-10-17
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>251 - Actual Concave Clearance</b>
Definition	Actual separation distance between Concave elements.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	3
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>252 - Minimum Concave Clearance</b>
Definition	Minimum separation distance between Concave elements.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-10-17
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>253 - Maximum Concave Clearance</b>
Definition	Maximum separation distance between Concave elements.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jaap van Bergeijk
Submit Date	2011-10-17
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>254 - Setpoint Separation Fan Rotational Speed</b>
Definition	Setpoint rotational speed of the fan used for separating product material from non product material.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Jaap van Bergeijk
Submit Date	2011-10-17
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>255 - Actual Separation Fan Rotational Speed</b>
Definition	Actual rotational speed of the fan used for separating product material from non product material.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	3
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>256 - Minimum Separation Fan Rotational Speed</b>
Definition	Minimum rotational speed of the fan used for separating product material from non product material.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Jaap van Bergeijk
Submit Date	2011-10-17
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>257 - Maximum Separation Fan Rotational Speed</b>
Definition	Maximum rotational speed of the fan used for separating product material from non product material.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Jaap van Bergeijk
Submit Date	2011-10-17
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>258 - Hydraulic Oil Temperature</b>
Definition	Temperature of fluid in the hydraulic system.
Comment	
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	mK - Temperature
Resolution	1
SAE SPN	
CANBus Range	0 - 2000000
Display Range	0 - 2000000
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO

Revision Number	3
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>259 - Yield Lag Ignore Time</b>
Definition	Amount of time to ignore yield data, starting at the transition from the in-work to the out-of-work state. During this time, the yield sensor provides inconsistent or unreliable crop flow data.
Comment	This DDE can be used to filter the yield data when creating yield maps. The values of the following list of DDE's may be inconsistent or unreliable during this yield lag ignore time: DDI's 83 to 91, 181 to 183 and 185 to 190.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	ms - Time
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	3
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>260 - Yield Lead Ignore Time</b>
Definition	Amount of time to ignore yield data, starting at the transition from the out-of-work to the in-work state. During this time, the yield sensor provides inconsistent or unreliable crop flow data.
Comment	This DDE can be used to filter the yield data when creating yield maps. The values of the following list of DDE's may be inconsistent or unreliable during this yield lead ignore time: DDI's 83 to 91, 181 to 183 and 185 to 190.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	ms - Time
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	3
Current Status	ISO-Published



Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>261 - Average Yield Mass Per Time</b>
Definition	Average Yield expressed as mass per unit time, not corrected for the reference moisture percentage DDI 184. This value is the average for a Task and may be reported as a total.
Comment	<p>This Average Yield Mass Per Time is the mass that includes the average crop moisture (DDI 262) if this is measured on e.g. harvesting equipment. This average yield mass per time is calculated as the yield total mass (DDI 90) divided by the effective total time (DDI 119) of the active task.</p> <p>When a task is resumed and its previously recorded totals are sent by the task controller to the connected working set, a situation can occur where there is a discrepancy between the yield total mass, the effective total time and the average yield mass per time values. In case all three of these DDI's are present in the device description and all three values are set by the task controller upon resuming a task, the working set shall compute its average yield mass per time from the yield total mass divided by the effective total time and shall discard the average yield mass per time value that it received from the task controller.</p>
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	2
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>262 - Average Crop Moisture</b>
Definition	Average Moisture of the harvested crop. This value is the average for a Task and may be reported as a total.
Comment	<p>This is the average of the actual crop moisture (DDI 99) for the active task and is calculated as an average based upon the yield total mass (DDI 90). In order to correctly calculate this value when a task is resumed, the yield total mass shall also be reported by the device as a total. When a task is resumed, the task controller sets both the yield total mass and the average crop moisture values. The device uses these values to derive the total moisture and calculate and report the new average crop moisture values for the resumed task.</p>

Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	3
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>263 - Average Yield Mass Per Area</b>
Definition	Average Yield expressed as mass per unit area, not corrected for the reference moisture percentage DDI 184. This value is the average for a Task and may be reported as a total.
Comment	<p>This Average Yield Mass Per Area is the mass that includes the average crop moisture (DDI 262) if this is measured on e.g. harvesting equipment. This average yield mass per area is calculated as the yield total mass (DDI 90) divided by the total area (DDI 116) of the active task.</p> <p>When a task is resumed and its previously recorded totals are sent by the task controller to the connected working set, a situation can occur where there is a discrepancy between the yield total mass, the total area and the average yield mass per area values. In case all three of these DDI's are present in the device description and all three values are set by the task controller upon resuming a task, the working set shall compute its average yield mass per area from the yield total mass divided by the total area and shall discard the average yield mass per area value that it received from the task controller.</p>
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Robert Waggoner
Submit Date	2011-07-08
Submit Company	AGCO
Revision Number	2
Current Status	ISO-Published
Status Date	2011-10-17
Status Comments	

<b>DD Entity</b>	<b>264 - Connector Pivot X-Offset</b>
Definition	X direction offset of a connector pivot point relative to DRP. This DDE shall be only attached to a DET element of type connector.
Comment	Some connector types are equipped with a pivot point which will influence the accuracy of applications as section control, prescription or sequence control. The Pivot X-Offset is used to define the distance from the device DRP to the connector pivot point in X direction.

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-03-07
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	
Attachment	<a href="#">2012-03-07: - ISO11783-11-DDI-264-Connector Pivot X-Offset-v1.pdf</a>

DD Entity	265 - Remaining Area
Definition	Remaining Area of a field, which is calculated from the total area and the processed area.
Comment	See DDI attachment for further details.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> <li>17 - Sensor System</li> </ul>
Unit Symbol	m <sup>2</sup> - Area
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Markus Eikler
Submit Date	2011-12-15
Submit Company	Mueller Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	
Attachment	<a href="#">2012-04-02: - ISO11783-11-DDI-265-Remaining Area-v1.pdf</a>

DD Entity	266 - Lifetime Application Total Mass
Definition	Entire Application Total Mass of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be settable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the settable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>

Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Approved
Status Date	2012-02-15
Status Comments	Status was approved

<b>DD Entity</b>	<b>267 - Lifetime Application Total Count</b>
Definition	Entire Application Total Count of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>268 - Lifetime Yield Total Volume</b>
Definition	Entire Yield Total Volume of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	L - Quantity per volume



Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>269 - Lifetime Yield Total Mass</b>
Definition	Entire Yield Total Mass of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>270 - Lifetime Yield Total Count</b>
Definition	Entire Yield Total Count of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops

Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>271 - Lifetime Total Area</b>
Definition	Entire Total Area of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> </ul>
Unit Symbol	m <sup>2</sup> - Area
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>272 - Lifetime Effective Total Distance</b>
Definition	Entire Total Distance of the device lifetime.

Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<p>1 - Tractor  2 - Primary Soil Tillage  3 - Secondary Soil Tillage  4 - Planters /Seeders  5 - Fertilizer  6 - Sprayers  7 - Harvesters  8 - Root Harvester  9 - Forage harvester  10 - Irrigation  11 - Transport / Trailers</p>
Unit Symbol	m - Distance
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-03-09
Status Comments	

<b>DD Entity</b>	<b>273 - Lifetime Ineffective Total Distance</b>
Definition	Entire Ineffective Total Distance of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<p>1 - Tractor</p> <p>2 - Primary Soil Tillage</p> <p>3 - Secondary Soil Tillage</p> <p>4 - Planters /Seeders</p> <p>5 - Fertilizer</p> <p>6 - Sprayers</p> <p>7 - Harvesters</p> <p>8 - Root Harvester</p> <p>9 - Forage harvester</p> <p>10 - Irrigation</p> <p>11 - Transport / Trailers</p>
Unit Symbol	m - Distance
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-03-09
Status Comments	

<b>DD Entity</b>	<b>274 - Lifetime Effective Total Time</b>
Definition	Entire Effective Total Time of the device lifetime.

Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<p>1 - Tractor  2 - Primary Soil Tillage  3 - Secondary Soil Tillage  4 - Planters /Seeders  5 - Fertilizer  6 - Sprayers  7 - Harvesters  8 - Root Harvester  9 - Forage harvester  10 - Irrigation  11 - Transport / Trailers  12 - Farmyard Work  13 - Powered Auxiliary Units  14 - Special Crops  15 - Municipal Work  17 - Sensor System</p>
Unit Symbol	s - Time count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>275 - Lifetime Ineffective Total Time</b>
Definition	Entire Ineffective Total Time of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmacyard Work</li> <li>13 - Powered Auxilary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> </ul>
Unit Symbol	s - Time count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>276 - Lifetime Fuel Consumption</b>
Definition	Entire Fuel Consumption of the device lifetime.



Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<p>1 - Tractor  2 - Primary Soil Tillage  3 - Secondary Soil Tillage  4 - Planters /Seeders  5 - Fertilizer  6 - Sprayers  7 - Harvesters  8 - Root Harvester  9 - Forage harvester  10 - Irrigation  11 - Transport / Trailers  12 - Farmyard Work  13 - Powered Auxiliary Units  14 - Special Crops  15 - Municipal Work</p>
Unit Symbol	L - Capacity count
Resolution	0,5
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 1073741823,5
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>277 - Lifetime Average Fuel Consumption per Time</b>
Definition	Entire Average Fuel Consumption per Time of the device lifetime.
Comment	<p>This is the overall average of the device. This average does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<p>1 - Tractor</p> <p>2 - Primary Soil Tillage</p> <p>3 - Secondary Soil Tillage</p> <p>4 - Planters /Seeders</p> <p>5 - Fertilizer</p> <p>6 - Sprayers</p> <p>7 - Harvesters</p> <p>8 - Root Harvester</p> <p>9 - Forage harvester</p> <p>10 - Irrigation</p> <p>11 - Transport / Trailers</p> <p>12 - Farmacyard Work</p> <p>13 - Powered Auxillary Units</p> <p>14 - Special Crops</p> <p>15 - Municipal Work</p>
Unit Symbol	mm <sup>3</sup> /s - Flow
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	
Submit Date	2012-01-09
Submit Company	
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>278 - Lifetime Average Fuel Consumption per Area</b>
Definition	Entire Average Fuel Consumption per Area of the device lifetime.

Comment	<p>This is the overall average of the device. This average does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<p>1 - Tractor  2 - Primary Soil Tillage  3 - Secondary Soil Tillage  4 - Planters /Seeders  5 - Fertilizer  6 - Sprayers  7 - Harvesters  8 - Root Harvester  9 - Forage harvester  10 - Irrigation  11 - Transport / Trailers  12 - Farmyard Work  13 - Powered Auxiliary Units  14 - Special Crops  15 - Municipal Work</p>
Unit Symbol	mm <sup>3</sup> /m <sup>2</sup> - Capacity per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>279 - Lifetime Yield Total Dry Mass</b>
Definition	Entire Yield Total Dry Mass of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>280 - Lifetime Yield Total Seed Cotton Mass</b>
Definition	Entire Yield Total Seed Cotton Mass of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	7 - Harvesters 14 - Special Crops
Unit Symbol	kg - Mass
Resolution	1

SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>281 - Lifetime Yield Total Lint Cotton Mass</b>
Definition	Entire Yield Total Lint Cotton Mass of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	7 - Harvesters 14 - Special Crops
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>282 - Lifetime Threshing Engagement Total Time</b>
Definition	Entire Threshing Engagement Total Time of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	s - Time count
Resolution	1

SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-09
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>283 - Precut Total Count</b>
Definition	The total number of pre-cutted product units produced by a device during an operation.
Comment	Precut Total Count is a total of a device element. It is intended to be used as a task based total value and therefore it is recommended to support the on-time and on-change trigger methods. The total trigger method and the setable property are required for this DDE.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-12
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>284 - Uncut Total Count</b>
Definition	The total number of un-cutted product units produced by a device during an operation.
Comment	Uncut Total Count is a total of a device element. It is intended to be used as a task based total value and therefore it is recommended to support the on-time and on-change trigger methods. The total trigger method and the setable property are required for this DDE.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-12
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	



<b>DD Entity</b>	<b>285 - Lifetime Precut Total Count</b>
Definition	Entire Precut Total Count of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-12
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

<b>DD Entity</b>	<b>286 - Lifetime Uncut Total Count</b>
Definition	Entire Uncut Total Count of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647

Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-01-12
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-02-15
Status Comments	

DD Entity	287 - Setpoint Prescription Mode
Definition	This DDE defines the source of the Task Controller set point value sent to the Control Function. This DDI shall be defined as DPD in the DDOP and needs to be setable. The TC shall then set this DDI before starting a prescription operation. The WS (Working Set) shall set this value to zero (0) after system start.
Comment	The Task Controller Prescription Mode shall have the following values: 0 = Unknown / not defined 1 = Prescription Rate 2 = Prescription Default 3 = Prescription GPS loss 4 = Prescription Out Of Field 5 = Manual Entry 6 = Peer Control 7 and higher are reserved for future assignments
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 6
Display Range	0 - 6
Submit by	Joe Tevis
Submit Date	2013-09-23
Submit Company	Topcon
Revision Number	2
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	
Attachment	<u><a href="#">2013-09-23: Prescription Mode and Control Function Mode Use Cases - Prescription Mode Supporting Doc-v1.ppt</a></u>

DD Entity	288 - Actual Prescription Mode
Definition	This DDE defines the actual source of the set point value used by the Control Function. This DDI shall be defined as DPD in the DDOP and shall not be setable and need to support the on change trigger. The TC should request this DDI in case of an active prescription operation for documentation purpose.

Comment	The Control Function Prescription Mode shall have one of the following values: 0 = Unknown / not defined 1 = TC rate 2 = Manual Entry 3 = Peer Control 4 = Max override 5 = Min override 6 and higher are reserved for future assignments
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 5
Display Range	0 - 5
Submit by	Joe Tevis
Submit Date	2013-09-23
Submit Company	Topcon
Revision Number	2
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>289 - Setpoint Work State</b>
Definition	The Setpoint Work State DDI is the control command counterparts to the Work State DDI (141). The separation of the control commands through one DDI from the actual state communicated through another DDI enables verification of the transmission of the control commands independent from the effectuation of the requested control action.
Comment	See DDI 290 attachment for implementation guideline.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 14 - Special Crops
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	Status was published

<b>DD Entity</b>	<b>290 - Setpoint Condensed Work State (1-16)</b>
------------------	---

Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 1 to 16 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	
Attachment	<a href="#">2016-04-05: - ISO11783-11-DDI-290-SetpointWorkState-v1.pdf</a>

<b>DD Entity</b>	<b>291 - Setpoint Condensed Work State (17-32)</b>
Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 17 to 32 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>292 - Setpoint Condensed Work State (33-48)</b>
------------------	--

Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 33 to 48 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	



<b>DD Entity</b>	<b>293 - Setpoint Condensed Work State (49-64)</b>
Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 49 to 64 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 14 - Special Crops
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>294 - Setpoint Condensed Work State (65-80)</b>
------------------	--

Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 65 to 80 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

DD Entity	295 - Setpoint Condensed Work State (81-96)
Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 81 to 96 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 14 - Special Crops
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

DD Entity	296 - Setpoint Condensed Work State (97-112)
-----------	--

Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 97 to 112 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>297 - Setpoint Condensed Work State (113-128)</b>
Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 113 to 128 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 14 - Special Crops
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	

<b>DD Entity</b>	<b>298 - Setpoint Condensed Work State (129-144)</b>
------------------	--

Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 129 to 144 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>299 - Setpoint Condensed Work State (145-160)</b>
Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 145 to 160 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 14 - Special Crops
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>300 - Setpoint Condensed Work State (161-176)</b>
------------------	--

Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 161 to 176 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	



<b>DD Entity</b>	<b>301 - Setpoint Condensed Work State (177-192)</b>
Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 177 to 192 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>302 - Setpoint Condensed Work State (193-208)</b>
------------------	--

Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 193 to 208 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>303 - Setpoint Condensed Work State (209-224)</b>
Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 209 to 224 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>304 - Setpoint Condensed Work State (225-240)</b>
------------------	--

Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 225 to 240 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	

<b>DD Entity</b>	<b>305 - Setpoint Condensed Work State (241-256)</b>
Definition	<p>The Setpoint Condensed Work State DDIs are the control command counterparts to the Condensed Work States DDIs (161 – 176).</p> <p>The value is a combination of the setpoint work states of individual sections or units (e.g. nozzles) number 241 to 256 into a single setpoint work state of their parent device element. The setpoint condensed work state contains the child element setpoint work states, in the driving direction from left to right, where the leftmost child element setpoint work state are the 2 lowest significant bits of the Process Data Value. Each child device elements setpoint work state is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element setpoint work states can be contained in one setpoint condensed work state of their parent device element. If less than 16 child device element setpoint work states are available, then the unused bits shall be set to value 11 (no change). When the parent device element contains the Setpoint Condensed Work State DDE, then the device descriptor shall not contain the individual setpoint work state DDEs in the child device elements.</p>
Comment	See the Setpoint Work State DDI (289) attachment for backwards compatibility and implementation guidelines.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jaap van Bergeijk
Submit Date	2012-01-19
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2012-04-02
Status Comments	Status was published

<b>DD Entity</b>	<b>306 - True Rotation Point X-Offset</b>
Definition	X direction offset of the device rotation point relative to the DRP.
Comment	For devices with more than one axle the rotation point can be located at another position within the device than the DRP. In this case, the True Rotation Point X and Y Offset DDIs shall be used to define the location of the rotation point on the device. Both DDI's shall be attached to the device element of type Device.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 14 - Special Crops 15 - Municipal Work
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-06-05
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-07-03
Status Comments	
Attachment	<a href="#">2012-07-03: - ISO11783-11-DDI-306-True Rotation Point-v1.pdf</a>

<b>DD Entity</b>	<b>307 - True Rotation Point Y-Offset</b>
Definition	Y direction offset of the device rotation point relative to the DRP.
Comment	For devices with more than one axle the rotation point can be located at another position within the device than the DRP. In this case, the True Rotation Point X and Y Offset DDIs shall be used to define the location of the rotation point on the device. Both DDI's shall be attached to the device element of type Device. See also attachment of True Rotation Point X-Offset, DDI 306.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 14 - Special Crops 15 - Municipal Work
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-06-05
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2012-07-03
Status Comments	

<b>DD Entity</b>	<b>308 - Actual Percentage Application Rate</b>
Definition	Actual Application Rate expressed as percentage
Comment	Counterpart to DDI 140 (Percentage Application Rate Setpoint)
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647

Display Range	0 - 2147483647
Submit by	Jan Steenbock
Submit Date	2012-06-05
Submit Company	98 - Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2012-07-03
Status Comments	



<b>DD Entity</b>	<b>309 - Minimum Percentage Application Rate</b>
Definition	Minimum Application Rate expressed as percentage
Comment	Supplied by device as physical minimum, see also DDI 140.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-07-03
Submit Company	John Deere
Revision Number	1
Current Status	Request Pending
Status Date	2012-07-03
Status Comments	

<b>DD Entity</b>	<b>310 - Maximum Percentage Application Rate</b>
Definition	Maximum Application Rate expressed as percentage
Comment	Supplied by device as physical maximum, see also DDI 140.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2012-07-03
Submit Company	John Deere
Revision Number	1
Current Status	Request Pending
Status Date	2012-07-03
Status Comments	

<b>DD Entity</b>	<b>311 - Relative Yield Potential</b>
Definition	Relative yield potential provided by a FMIS or a sensor or entered by the operator for a certain task expressed as percentage.
Comment	Relative yield potential could be used as input for an intelligent unit to calculate the appropriate amount of fertilizer / seed / etc. more accurate. Typical range is 80 to 120%. Expressed in ppm this is 800,000 to 1,200,000.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Martin Sperlich
Submit Date	2012-07-26
Submit Company	CLAAS Agrosystems GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2012-08-27
Status Comments	

<b>DD Entity</b>	<b>312 - Minimum Relative Yield Potential</b>
Definition	Minimum potential yield expressed as percentage.
Comment	This DDIs is used by the system to provide information about its value range support for relative yield potential.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Martin Sperlich
Submit Date	2012-07-29
Submit Company	CLAAS Agrosystems GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2012-08-27
Status Comments	

<b>DD Entity</b>	<b>313 - Maximum Relative Yield Potential</b>
Definition	Maximum potential yield expressed as percentage.
Comment	This DDIs is used by the system to provide information about its value range support for relative yield potential.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Martin Sperlich
Submit Date	2012-08-27
Submit Company	CLAAS Agrosystems GmbH & Co. KG
Revision Number	1
Current Status	Request Pending
Status Date	2012-08-27
Status Comments	

<b>DD Entity</b>	<b>314 - Actual Percentage Crop Dry Matter</b>
Definition	Actual Percentage Crop Dry Matter expressed as parts per million.
Comment	This DDE defines the actual percentage of dry matter in the harvested crop.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 17 - Sensor System
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Martin Sperlich
Submit Date	2012-09-17
Submit Company	CLAAS Agrosystems GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2012-09-24
Status Comments	

<b>DD Entity</b>	<b>315 - Average Percentage Crop Dry Matter</b>
Definition	Average Percentage Crop Dry Matter expressed as parts per million.
Comment	This DDE defines the average percentage of dry matter in the harvested crop.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 17 - Sensor System
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Martin Sperlich
Submit Date	2012-09-17
Submit Company	CLAAS Agrosystems GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2012-09-24
Status Comments	

<b>DD Entity</b>	<b>316 - Effective Total Fuel Consumption</b>
Definition	Accumulated total fuel consumption in working position.
Comment	
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Martin Sperlich
Submit Date	2012-09-17
Submit Company	CLAAS Agrosystems GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2012-09-24
Status Comments	

<b>DD Entity</b>	<b>317 - Ineffective Total Fuel Consumption</b>
Definition	Accumulated total fuel consumption in non working position.
Comment	
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Martin Sperlich
Submit Date	2012-09-17
Submit Company	CLAAS Agrosystems GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2012-09-24
Status Comments	

<b>DD Entity</b>	<b>318 - Effective Total Diesel Exhaust Fluid Consumption</b>
Definition	Accumulated total Diesel Exhaust Fluid consumption in working position.
Comment	Example: Diesel Exhaust Fluid as specified per ISO22241.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647

Submit by	Martin Sperlich
Submit Date	2012-09-17
Submit Company	CLAAS Agrosystems GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2012-09-24
Status Comments	

<b>DD Entity</b>	<b>319 - Ineffective Total Diesel Exhaust Fluid Consumption</b>
Definition	Accumulated total Diesel Exhaust Fluid consumption in non working position.
Comment	Example: Diesel Exhaust Fluid as specified per ISO22241.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Martin Sperlich
Submit Date	2012-09-24
Submit Company	CLAAS Agrosystems GmbH & Co. KG
Revision Number	1
Current Status	Request Pending
Status Date	2012-09-24
Status Comments	

<b>DD Entity</b>	<b>320 - Last loaded Weight</b>
Definition	Last loaded Weight value specified as mass
Comment	After a loading Procedure, this DDI sends the loaded Mass.  For more information see attachment located at Last loaded Weight DDE
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger

Submit Date	2013-01-14
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2013-02-04
Status Comments	
Attachment	<u><a href="#">2013-02-28: Fix of typo and DDI number correction in DDI table - ISO 11783-11-DDI 320-Weighing Load Unload-v3.pdf</a></u>



<b>DD Entity</b>	<b>321 - Last unloaded Weight</b>
Definition	Last unloaded Weight value specified as mass
Comment	After a unloading Procedure, this DDI sends the unloaded Mass.  For more information see attachment located at Last loaded Weight DDE
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2013-01-14
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2013-02-04
Status Comments	

<b>DD Entity</b>	<b>322 - Load Identification Number</b>
Definition	The Load Identification Number as a decimal number in the range of 0 to 4294967295. Note that the value of this DDI has the limitation of being an unsigned 32 bit number.
Comment	The DDI Load Identification Number can be used together with the DDI "320 - Last loaded Weight" to document the loading of material on a weighing system. See also the attached document for more details.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 14 - Special Crops 17 - Sensor System
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	

CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Franz Hoepfinger
Submit Date	2013-05-21
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2013-07-15
Status Comments	
Attachment	<u>2013-09-22: -</u> <u>ISO11783-11-DDI-322-Load Identification Number v1-v2.pdf</u>

<b>DD Entity</b>	<b>323 - Unload Identification Number</b>
Definition	The Unload Identification Number as a decimal number in the range of 0 to 2147483647. Note that the value of this DDI has the limitation of being an unsigned 32 bit number.
Comment	The DDI Unload Identification Number can be used together with the DDI "321 - Last Unloaded Weight" to document the unloading of material on a weighing system. See also the attached document for more details.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 14 - Special Crops 17 - Sensor System
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2013-07-15
Submit Company	367 - Fliegl Agratechnik GmbH
Revision Number	1
Current Status	Request Pending
Status Date	2013-07-15
Status Comments	
Attachment	<a href="#">2013-07-15: - ISO11783-11-DDI-323-Unload Identification Number v1-v1.pdf</a>

<b>DD Entity</b>	<b>324 - Chopper Engagement Total Time</b>
Definition	Accumulated time while the chopping mechanism is engaged
Comment	This DDE represents the total engagement time of the chopping mechanism of the machine and is recommended to be used at maximum once within the device description in the device element that represents the machine.  This DDE is designated for the chopping unit of a forage harvester. It could be also used for the straw chopper of a harvester. For combine harvesters please also see DDE 236 Threshing Engagement Total Time.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops

Unit Symbol	s - Time count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Martin Sperlich
Submit Date	2013-06-17
Submit Company	CLAAS Agrosystems KGaA mbH & Co KG
Revision Number	1
Current Status	ISO-Published
Status Date	2013-07-15
Status Comments	

<b>DD Entity</b>	<b>325 - Lifetime Application Total Volume</b>
Definition	Entire Application Total Volume of the device lifetime.
Comment	This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be settable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value. The Working Set Master shall support the total trigger method for this DDE but shall not support the settable property. The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 9 - Forage harvester 10 - Irrigation
Unit Symbol	L - Capacity count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Michael Köcher
Submit Date	2013-09-02
Submit Company	AMAZONE
Revision Number	1
Current Status	ISO-Published
Status Date	2013-09-27
Status Comments	

<b>DD Entity</b>	<b>326 - Setpoint Header Speed</b>
Definition	The setpoint rotational speed of the header attachment of a chopper, mower or combine
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops 15 - Municipal Work
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2015-11-27
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1

Current Status	ISO-Published
Status Date	2013-12-04
Status Comments	

DD Entity	327 - Actual Header Speed
Definition	The actual rotational speed of the header attachment of a chopper, mower or combine
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops 15 - Municipal Work
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2013-12-04
Status Comments	

DD Entity	328 - Minimum Header Speed
Definition	The minimum rotational speed of the header attachment of a chopper, mower or combine
Comment	This is a value recommended by the manufacturer of the machine as the minimum speed (unlike 0) for a proper working
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops 15 - Municipal Work
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>329 - Maximum Header Speed</b>
Definition	The maximum rotational speed of the header attachment of a chopper, mower or combine
Comment	This is a value recommended by the manufacturer of the machine as the maximum speed the machine is able to offer
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops 15 - Municipal Work
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>330 - Setpoint Cutting drum speed</b>
Definition	The setpoint speed of the cutting drum of a chopper
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops 15 - Municipal Work
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	



<b>DD Entity</b>	<b>331 - Actual Cutting drum speed</b>
Definition	The actual speed of the cutting drum of a chopper
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops 15 - Municipal Work
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>332 - Minimum Cutting drum speed</b>
Definition	The minimum speed of the cutting drum of a chopper
Comment	This is a value recommended by the manufacturer of the machine as the minimum speed (unlike 0) for a proper working
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops 15 - Municipal Work
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483,647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>333 - Maximum Cutting drum speed</b>
Definition	The maximum speed of the cutting drum of a chopper
Comment	This is a value recommended by the manufacturer of the machine as the maximum speed the machine is able to offer
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops 15 - Municipal Work
Unit Symbol	/s - Quantity per time unit
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>334 - Operating Hours Since Last Sharpening</b>
Definition	This value describes the working hours since the last sharpening of the cutting device.
Comment	As the sharpness of the cutting drums cutters on a harvester is an important indicator for cutting quality and an important factor for the fuel usage, this value provides information about quality and effectivity of the harvesting process
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 12 - Farmyard Work 14 - Special Crops 15 - Municipal Work
Unit Symbol	s - Time count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>335 - Front PTO hours</b>
Definition	The hours the Front PTO of the machine was running for the current Task
Comment	This value provides information of the active working time for example of the header attachment of a selfpropelled machine
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	s - Time count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>336 - Rear PTO hours</b>
Definition	The hours the Rear PTO of the machine was running for the current Task
Comment	This value provides information of the active working time for example of the header attachment of a selfpropelled machine

Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	s - Time count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2014-01-17
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>337 - Lifetime Front PTO hours</b>
Definition	The hours the Front PTO of the machine was running for the lifetime of the machine
Comment	This value provides information of the active working time for example of the header attachment of a selfpropelled machine
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 12 - Farmyard Work 14 - Special Crops 15 - Municipal Work
Unit Symbol	h - Hour
Resolution	0,1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,0 - 214748364,7
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>338 - Lifetime Rear PTO Hours</b>
Definition	The hours the Rear PTO of the machine was running for the lifetime of the machine
Comment	This value provides information of the active working time for example of the header attachment of a selfpropelled machine

Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	h - Hour
Resolution	0,1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,0 - 214748364,7
Submit by	Meyer Matthias
Submit Date	2014-01-17
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>339 - Effective Total Loading Time</b>
Definition	The total time needed in the current task to load a product such as crop.
Comment	
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester 11 - Transport / Trailers 12 - Farmyard Work
Unit Symbol	s - Time count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>340 - Effective Total Unloading Time</b>
Definition	The total time needed in the current task to unload a product crop.
Comment	
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 12 - Farmyard Work
Unit Symbol	s - Time count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-01-17
Status Comments	

<b>DD Entity</b>	<b>341 - Setpoint Grain Kernel Cracker Gap</b>
Definition	The setpoint gap (distance) of the grain kernel cracker drums in a chopper.
Comment	The gap (distance) of the grain kernel cracker is an indicator to the quality of chopped corn.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2013-12-04
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2014-02-24
Status Comments	

<b>DD Entity</b>	<b>342 - Actual Grain Kernel Cracker Gap</b>
Definition	The actual gap (distance) of the grain kernel cracker drums in a chopper
Comment	The actual gap (distance) of the grain kernel cracker is an indicator to the quality of chopped corn.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2014-02-25
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-02-25
Status Comments	



<b>DD Entity</b>	<b>343 - Minimum Grain Kernel Cracker Gap</b>
Definition	The minimum gap (distance) of the grain kernel cracker drums in a chopper
Comment	The minimum gap (distance) of the grain kernel cracker that can be adjusted
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2014-02-25
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-02-25
Status Comments	

<b>DD Entity</b>	<b>344 - Maximum Grain Kernel Cracker Gap</b>
Definition	The maximum gap (distance) of the grain kernel cracker drums in a chopper
Comment	The maximum gap (distance) of the grain kernel cracker that can be adjusted.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2014-02-25
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-02-25
Status Comments	

<b>DD Entity</b>	<b>345 - Setpoint Swathing Width</b>
Definition	This is the setpoint swathing width of the swath created by a raker.
Comment	For mowers the working width DDIs will represent the width of the mower whereas swathing width will represent the swath with created by the mover.
Typically used by Device Class(es)	0 - Non-specific system 7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2014-03-17
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-03-25
Status Comments	

<b>DD Entity</b>	<b>346 - Actual Swathing Width</b>
Definition	This is the width of the swath currently created by a raker.
Comment	For mowers the working width DDIs will represent the width of the mower whereas swathing width will represent the swath width created by the mover.
Typically used by Device Class(es)	0 - Non-specific system 7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2014-03-17
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-03-25
Status Comments	

<b>DD Entity</b>	<b>347 - Minimum Swathing Width</b>
Definition	This is the minimum swath width the raker can create.
Comment	For mowers the working width DDIs will represent the width of the mower whereas swathing width will represent the swath width created by the mover.
Typically used by Device Class(es)	0 - Non-specific system 7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2014-03-17
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-03-25
Status Comments	

<b>DD Entity</b>	<b>348 - Maximum Swathing Width</b>
Definition	This is the maximum with of the swath the raker can create.
Comment	For mowers the working width DDIs will represent the width of the mower whereas swathing width will represent the swath width created by the mover.
Typically used by Device Class(es)	0 - Non-specific system 7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2014-03-17
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-03-25
Status Comments	

<b>DD Entity</b>	<b>349 - Nozzle Drift Reduction</b>
Definition	The Nozzle Drift Reduction classification value of the spraying equipment as percentage
Comment	The use of this DDE is to document the current used drift reducing classification of the nozzles or combination of drift reducing technique as percentage value. To record documentation obligation product during applying in adjacency of sensitive areas. For more information about nozzle drift classification see also Standard ISO 22369-1 "Crop protection equipment - Drift classification of spraying equipment"
Typically used by Device Class(es)	6 - Sprayers
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 100
Display Range	0 - 100
Submit by	Matthias Meyer
Submit Date	2014-06-18
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2014-06-18
Status Comments	

<b>DD Entity</b>	<b>350 - Function or Operation Technique</b>
Definition	The Function or Operation Technique DDE can be used to define the operation technique or functionality performed by a device element defined within the DDOP. The values to be used are defined in the attached document.
Comment	In a DDOP (Device Description Object Pool) of an ISOBUS device there are different functionalities covered. The device element types in the Task Controller standard which are Device, Function, Bin, Section, Unit, Connector Type, and Navigation Reference do not last out for certain or more complex devices to describe all information in a unique way to the Task Controller Server. For more information see the attached document.

Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2014-07-01
Submit Company	John Deere
Revision Number	1
Current Status	Not Specified
Status Date	2016-12-12
Status Comments	
Attachment	<a href="#">2017-04-03: - ISO11783-11-DDI-350-Function and Operation Technique Type v3-v3.pdf</a>

<b>DD Entity</b>	<b>351 - Application Total Volume in [ml]</b>
Definition	Accumulated Application specified as volume in milliliter [ml]
Comment	is a counter of a device element
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2014-07-02
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2014-07-02
Status Comments	

<b>DD Entity</b>	<b>352 - Application Total Mass in gram [g]</b>
Definition	Accumulated Application specified as mass in gram [g]
Comment	is a counter of a device element
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 10 - Irrigation
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Meyer
Submit Date	2014-07-02
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2014-07-02
Status Comments	

<b>DD Entity</b>	<b>353 - Total Application of Nitrogen</b>
Definition	Accumulated application of nitrogen [N2] specified as gram [g]
Comment	This total is a counter of a device element
Typically used by Device Class(es)	5 - Fertilizer
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Christoph Staub
Submit Date	2014-06-04
Submit Company	Zunhammer
Revision Number	1
Current Status	ISO-Published
Status Date	2014-08-26
Status Comments	Status was published

<b>DD Entity</b>	<b>354 - Total Application of Ammonium</b>
Definition	Accumulated application of ammonium [NH4] specified as gram [g]
Comment	This total is a counter of a device element
Typically used by Device Class(es)	5 - Fertilizer
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Christoph Staub
Submit Date	2014-06-04
Submit Company	Zunhammer GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-08-26
Status Comments	Status was published

<b>DD Entity</b>	<b>355 - Total Application of Phosphor</b>
Definition	Accumulated application of phosphor (P2O5) specified as gram [g]
Comment	This total is a counter of a device element
Typically used by Device Class(es)	5 - Fertilizer
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Christoph Staub
Submit Date	2014-06-04
Submit Company	Zunhammer GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-08-26
Status Comments	Status was published

<b>DD Entity</b>	<b>356 - Total Application of Potassium</b>
Definition	Accumulated application of potassium (K2) specified as gram [g]
Comment	This total is a counter of a device element
Typically used by Device Class(es)	5 - Fertilizer
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Christoph Staub
Submit Date	2014-06-04
Submit Company	Zunhammer GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-08-26
Status Comments	Status was published



<b>DD Entity</b>	<b>357 - Total Application of Dry Matter</b>
Definition	Accumulated application of dry matter in kilogram [kg]. Dry matter measured at zero percent of moisture
Comment	This total is a counter of a device element
Typically used by Device Class(es)	5 - Fertilizer
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Christoph Staub
Submit Date	2014-06-04
Submit Company	Zunhammer GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2014-08-26
Status Comments	Status was published

<b>DD Entity</b>	<b>358 - Average Dry Yield Mass Per Time</b>
Definition	Average Yield expressed as mass per unit time, corrected for the reference moisture percentage DDI 184. This value is the average for a Task and may be reported as a total.
Comment	This Average Dry Yield Mass Per Time is the mass flow that has been corrected for the average crop moisture (DDI 262) based on the reference moisture for dry mass (DDI 184). This is the "dry" equivalent to DDI 261. This average yield mass per time is calculated as the yield total dry mass (DDI 183) divided by the effective total time (DDI 119) of the active task. When resuming a task, the working set shall compute its average dry yield mass per time from the yield total mass (DDI 90), average crop moisture (DDI 262), reference moisture percentage (DDI 184), and effective total time (119) assuming these DDI's are sent by the task controller.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mg/s - Mass flow
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Tony Woodcock
Submit Date	2014-08-08
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Published

Status Date	2014-08-26
Status Comments	Status was published

<b>DD Entity</b>	<b>359 - Average Dry Yield Mass Per Area</b>
Definition	Average Yield expressed as mass per unit area, corrected for the reference moisture percentage DDI 184. This value is the average for a Task and may be reported as a total.
Comment	This Average Dry Yield Mass Per Area is the mass flow that has been corrected for the average crop moisture (DDI 262) based on the reference moisture for dry mass (DDI 184). This is the "dry" equivalent to DDI 263. This average yield mass per area is calculated as the yield total dry mass (DDI 183) divided by the total area (DDI 116) of the active task. When resuming a task, the working set shall compute its average dry yield mass per area from the yield total mass (DDI 90), average crop moisture (DDI 262), reference moisture percentage (DDI 184), and total area (DDI 116) assuming these DDI's are sent by the task controller.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Tony Woodcock
Submit Date	2014-08-08
Submit Company	Ag Leader Technology
Revision Number	1
Current Status	ISO-Published
Status Date	2014-08-26
Status Comments	

<b>DD Entity</b>	<b>360 - Last Bale Size</b>
Definition	The bale size of the most recently produced bale. Bale Size as length for a square baler or diameter for a round baler.
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler can add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647

Display Range	0 - 2147483647
Submit by	Lynn Derynck
Submit Date	2014-11-07
Submit Company	CNH Industrial N.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2014-12-03
Status Comments	

<b>DD Entity</b>	<b>361 - Last Bale Density</b>
Definition	The bale density of the most recently produced bale.  Unit: mg/l (mass per unit volume)
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler can add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	mg/l - Mass per capacity unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Lynn Derynck
Submit Date	2014-11-07
Submit Company	CNH Industrial N.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2014-12-03
Status Comments	

<b>DD Entity</b>	<b>362 - Total Bale Length</b>
Definition	Gives the total baled meters during a task. This is calculated as the sum of the lengths of all knotted bales (square baler).
Comment	
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Lynn Derynck
Submit Date	2014-11-07
Submit Company	CNH Industrial N.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2014-12-03
Status Comments	
Attachment	2014-11-07: - ISO 11783-11 DDIdentifier Total Bale Length-v1.doc

<b>DD Entity</b>	<b>363 - Last Bale Dry Mass</b>
Definition	The dry mass of the bale that has most recently been produced. This is the bale mass corrected for the average moisture of this bale (DDI 212).
Comment	The recommended use of this DDE is for a baler to report this once for every bale that is produced. A baler may add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE after the bale is produced. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale is produced and leaves the machine.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	g - Mass large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Lynn Derynck
Submit Date	2014-11-07
Submit Company	CNH Industrial N.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2014-12-03
Status Comments	
Attachment	<a href="#">2014-11-07: - ISO 11783-11 DDIdentifier Last Bale Mass Dry-v1.doc</a>

<b>DD Entity</b>	<b>364 - Actual Flake Size</b>
Definition	Actual size of the flake that is currently produced by the chamber.
Comment	The recommended use of this DDE is for a baler to report this once for each new flake that entered the baler chamber and obtained at the maximum compression of the plunger. A baler may add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE at each new flake.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 1000
Display Range	0 - 1000
Submit by	Lynn Derynck
Submit Date	2014-11-07
Submit Company	CNH Industrial N.V.
Revision Number	1

Current Status	ISO-Published
Status Date	2015-01-13
Status Comments	
Attachment	2014-11-07: - ISO 11783-11 DDIdentifier Flake Size-v1.doc

<b>DD Entity</b>	<b>365 - Setpoint Downforce Pressure</b>
Definition	Setpoint downforce pressure for an operation
Comment	This value represents the system pressure to produce the downforce (or upforce) for an operation measured in Pa (Pascal); In case of an negative value the system pressure would produce Upforce.
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	Pa - Pressure
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Brandon McDonald
Submit Date	2014-12-04
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2015-01-13
Status Comments	

<b>DD Entity</b>	<b>366 - Actual Downforce Pressure</b>
Definition	Actual downforce pressure for an operation
Comment	This value represents the actual system pressure to produce the downforce (or upforce) for an operation measured in Pa (Pascal); In case of an negative value the system pressure would produce Upforce.
Typically used by Device Class(es)	2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer
Unit Symbol	Pa - Pressure
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Brandon McDonald
Submit Date	2014-12-04
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2015-01-13
Status Comments	



<b>DD Entity</b>	<b>367 - Condensed Section Override State (1-16)</b>
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 1 to 16 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> </ul>
Unit Symbol	not defined - not defined
Resolution	1

SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2014-11-18
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>368 - Condensed Section Override State (17-32)</b>
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 17 to 32 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-20
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>369 - Condensed Section Override State (33-48)</b>
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 33 to 48 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> </ul>
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	

CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-20
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>370 - Condensed Section Override State (49-64)</b>
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 49 to 64 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-20
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

DD Entity	371 - Condensed Section Override State (65-80)
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 65 to 80 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers “on change” and “time based”. The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>372 - Condensed Section Override State (81-96)</b>
------------------	---



Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 81 to 96 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers “on change” and “time based”. The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

DD Entity	373 - Condensed Section Override State (97-112)
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 97 to 112 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers “on change” and “time based”. The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>374 - Condensed Section Override State (113-128)</b>
------------------	---

Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 113 to 128 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers “on change” and “time based”. The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

DD Entity	375 - Condensed Section Override State (129-144)
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 129 to 144 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>376 - Condensed Section Override State (145-160)</b>
------------------	---



Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 145 to 160 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> </ul>
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295

Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>377 - Condensed Section Override State (161-176)</b>
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 161 to 176 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> </ul>
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	

CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>378 - Condensed Section Override State (177-192)</b>
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 177 to 192 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>379 - Condensed Section Override State (193-208)</b>
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 193 to 208 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> </ul>
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	

CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>380 - Condensed Section Override State (209-224)</b>
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 209 to 224 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published



<b>DD Entity</b>	<b>381 - Condensed Section Override State (225-240)</b>
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 225 to 240 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> </ul>
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	

CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>382 - Condensed Section Override State (241-256)</b>
Definition	<p>This DDE is used by the implement to communicate that a certain section is overridden and will not follow the section control commands. The value is a combination of the override states of individual sections number 241 to 256 into a single override state. The condensed section override state contains the child element override states, in the driving direction from left to right, where the leftmost child element override state are the 2 lowest significant bits of the Process Data Value. Each child device elements override state is represented by 2 bits and defined as: 00 = section is not overridden, 01 = section is overridden, 10 = reserved, 11 = undefined / not installed. In total 16 child device element override states can be contained in one condensed section override state. If less than 16 child device element override states are available, then the unused bits shall be set to value 11 (undefined / not installed). This DDE shall be placed in the same device element as the corresponding actual condensed work state.</p>
Comment	<p>It is common for SC servers to show the current state of the sections in a proprietary screen. As the implement is allowed to override the commanded state from the task controller it is impossible for the operator to predict what happens when driving into an unworked area. With this DDE it is possible for the SC server to show overridden sections in the proprietary screen.</p> <p>This DDE shall be defined as DPD in the DDOP of the implement. The DPD shall at least support the datalog triggers "on change" and "time based". The value shall only be sent by the implement if it was requested (single request or datalog trigger) by the TC-SC server.</p>

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Michael Köcher
Submit Date	2015-01-21
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-27
Status Comments	Status was published

<b>DD Entity</b>	<b>383 - Apparent Wind Direction</b>
Definition	The apparent wind is the wind which is measured on a moving vehicle. It is the result of two motions: the actual true wind and the motion of the vehicle. The wind angle is referenced to the present heading of the vehicle (Zero degree refers to the vehicle driving direction).
Comment	DDI 207 defines the true wind. DDI 208 defines the true wind angle.
Typically used by Device Class(es)	0 - Non-specific system
Unit Symbol	° - Angle
Resolution	1
SAE SPN	
CANBus Range	0 - 359
Display Range	0 - 359
Submit by	Jan Steenbock
Submit Date	2015-01-12
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2015-02-10
Status Comments	

<b>DD Entity</b>	<b>384 - Apparent Wind Speed</b>
Definition	The apparent wind is the wind which is measured on a moving vehicle. It is the result of two motions: the actual true wind and the motion of the vehicle.
Comment	DDI 207 defines the true wind. DDI 208 defines the true wind angle.
Typically used by Device Class(es)	0 - Non-specific system 17 - Sensor System
Unit Symbol	mm/s - Speed
Resolution	1
SAE SPN	
CANBus Range	0 - 100000000
Display Range	0 - 100000000
Submit by	Jan Steenbock
Submit Date	2015-01-12
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2015-02-10
Status Comments	

<b>DD Entity</b>	<b>385 - MSL Atmospheric Pressure</b>
Definition	The atmospheric pressure MSL (Mean Sea Level) is the air pressure related to mean sea level.
Comment	In weather charts only the converted pressure to mean sea level is indicated. Only the pressure changes due to the weather has to be considered.
Typically used by Device Class(es)	0 - Non-specific system 17 - Sensor System
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	0 - 2000000
Display Range	0,0 - 200000,0
Submit by	Jan Steenbock
Submit Date	2015-03-30
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-03-30
Status Comments	

<b>DD Entity</b>	<b>386 - Actual Atmospheric Pressure</b>
Definition	The Actual Atmospheric Pressure is the air pressure currently measured by the weather station.
Comment	This value does take the current altitude (field position) into count.
Typically used by Device Class(es)	0 - Non-specific system 17 - Sensor System
Unit Symbol	Pa - Pressure
Resolution	0,1
SAE SPN	
CANBus Range	0 - 2000000
Display Range	0,0 - 200000,0
Submit by	Jan Steenbock
Submit Date	2015-03-30
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-03-30
Status Comments	

<b>DD Entity</b>	<b>387 - Total Revolutions in Fractional Revolutions</b>
Definition	Accumulated Revolutions specified with fractional revolutions
Comment	Forward or Clockwise rotation represented as positive numbers and reverse or Counter-Clockwise rotation represented by negative numbers. To prevent rounding errors the basic unit r/min where chosen.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	# - Quantity/Count
Resolution	0,0001
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748,3648 - 214748,3647
Submit by	Mike Schmidt
Submit Date	2015-04-24
Submit Company	AGCO Corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2015-04-24
Status Comments	

<b>DD Entity</b>	<b>388 - Total Revolutions in Complete Revolutions</b>
Definition	Accumulated Revolutions specified as completed integer revolutions
Comment	Forward or Clockwise rotation represented as positive numbers and reverse or Counter-Clockwise rotation represented by negative numbers.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Mike Schmidt
Submit Date	2015-04-24
Submit Company	AGCO Corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2015-04-24
Status Comments	

<b>DD Entity</b>	<b>389 - Setpoint Revolutions specified as count per time</b>
Definition	Setpoint Revolutions specified as count per time
Comment	Forward or Clockwise rotation represented as positive numbers and reverse or Counter-Clockwise rotation represented by negative numbers. To prevent rounding errors the basic unit r/min where chosen.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	r/min - Revolutions per minute
Resolution	0,0001
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748,3648 - 214748,3647
Submit by	David Kuhnel
Submit Date	2015-04-24
Submit Company	DICKEY-john Corp
Revision Number	1
Current Status	ISO-Published
Status Date	2015-04-24
Status Comments	

<b>DD Entity</b>	<b>390 - Actual Revolutions Per Time</b>
Definition	Actual Revolutions specified as count per time
Comment	Forward or Clockwise rotation represented as positive numbers and reverse or Counter-Clockwise rotation represented by negative numbers. To prevent rounding errors the basic unit r/min where chosen.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	r/min - Revolutions per minute
Resolution	0,0001
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748,3648 - 214748,3647
Submit by	David Kuhnel
Submit Date	2015-03-23
Submit Company	DICKEY-john Corp
Revision Number	1
Current Status	ISO-Published
Status Date	2015-03-23
Status Comments	

<b>DD Entity</b>	<b>391 - Default Revolutions Per Time</b>
Definition	Default Revolutions specified as count per time
Comment	Forward or Clockwise rotation represented as positive numbers and reverse or Counter-Clockwise rotation represented by negative numbers. To prevent rounding errors the basic unit r/min where chosen.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	r/min - Revolutions per minute
Resolution	0,0001
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748,3648 - 214748,3647
Submit by	David Kuhnel
Submit Date	2015-03-23
Submit Company	DICKEY-john Corp
Revision Number	1
Current Status	ISO-Published
Status Date	2015-03-23
Status Comments	

<b>DD Entity</b>	<b>392 - Minimum Revolutions Per Time</b>
Definition	Minimum Revolutions specified as count per time
Comment	Forward or Clockwise rotation represented as positive numbers and reverse or Counter-Clockwise rotation represented by negative numbers. To prevent rounding errors the basic unit r/min where chosen.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	r/min - Revolutions per minute
Resolution	0,0001
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748,3648 - 214748,3647
Submit by	David Kuhnel
Submit Date	2015-03-23
Submit Company	DICKEY-john Corp
Revision Number	1
Current Status	ISO-Published
Status Date	2015-03-23
Status Comments	



DD Entity	393 - Maximum Revolutions Per Time
Definition	Maximum Revolutions specified as count per time
Comment	Forward or Clockwise rotation represented as positive numbers and reverse or Counter-Clockwise rotation represented by negative numbers. To prevent rounding errors the basic unit r/min where chosen.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers
Unit Symbol	r/min - Revolutions per minute
Resolution	0,0001
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-214748,3648 - 214748,3647
Submit by	David Kuhnel
Submit Date	2015-07-02
Submit Company	DICKEY-john Corp
Revision Number	1
Current Status	ISO-Published
Status Date	2015-07-02
Status Comments	

DD Entity	394 - Actual Fuel Tank Content
Definition	The actual content of the fuel tank
Comment	This value can be used to see the refilling of the fuel tank or the theft of fuel.
Typically used by Device Class(es)	1 - Tractor 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Hans van Zadelhoff
Submit Date	2015-07-02
Submit Company	Grimme Landmaschinenfabrik GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-09-05
Status Comments	Status was published

<b>DD Entity</b>	<b>395 - Actual Diesel Exhaust Fluid Tank Content</b>
Definition	The actual content of the diesel exhaust fluid tank
Comment	This value can be used to see the refilling of the diesel exhaust fluid tank or the theft of diesel exhaust fluid.
Typically used by Device Class(es)	1 - Tractor 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Hans van Zadelhoff
Submit Date	2015-07-02
Submit Company	Grimme Landmaschinenfabrik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-07-02
Status Comments	

<b>DD Entity</b>	<b>396 - Setpoint Speed</b>
Definition	The setpoint speed that can be specified in a process data variable for communication between farm management information systems and mobile implement control systems. The setpoint speed DDI may also be used in a device description object pool to specify support for speed control by a device. A positive value will represent forward direction and a negative value will represent reverse direction.
Comment	The implementation of speed control on the mobile implement control system may use other ISO11783 network parameter groups (e.g. ISO11783-7 Commanded Vehicle Speed and Machine Selected Speed Setpoint) and may be subject to control request authentication requirements. The definition of this DDI has been added to the ISO 11783-11 data dictionary to facilitate the specification of a setpoint speed in a task data transfer file and to enable specification of the support of speed control in a device description object pool.

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops
Unit Symbol	mm/s - Speed
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Hans van Zadelhoff
Submit Date	2015-02-12
Submit Company	Grimme Landmaschinenfabrik GmbH & Co. KG
Revision Number	3
Current Status	ISO-Published
Status Date	2015-04-24
Status Comments	

DD Entity	397 - Actual Speed
Definition	The actual speed as measured on or used by a device for the execution of task based data, e.g. to convert a setpoint rate expressed per area to device specific control data that is expressed as a rate per time. The actual speed can be measured by the device itself or it can be a speed value that is obtained from one of the speed parameter groups that are broadcasted on the ISO11783 network and defined in ISO11783-7. Examples of broadcasted speed parameter groups are wheel based speed, ground based speed and machine selected speed. The source of the actual speed can be specified by a Speed Source DDI that is present in the same device element as the speed DDI. A positive value will represent forward direction and a negative value will represent reverse direction.
Comment	This DDI has been added to the data dictionary to support logging of the speed that the device uses for processing and for generation of task data. The addition of a DDI for actual speed allows speed values to be added to the default data set that devices present to a task controller or a data logger.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops
Unit Symbol	mm/s - Speed
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Hans van Zadelhoff
Submit Date	2015-04-24
Submit Company	Grimme Landmaschinenfabrik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-04-24
Status Comments	

DD Entity	398 - Minimum Speed
-----------	---------------------

Definition	The minimum speed that can be specified in a process data variable for communication between farm management information systems and mobile implement control systems. A positive value will represent forward direction and a negative value will represent reverse direction.
Comment	This DDI has been added to the data dictionary to support the setting and logging of a minimum speed for a part of a device. See also the definitions of the Setpoint, Actual and Maximum Speed DDIs for additional definition and implementation information of Speed DDIs.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	mm/s - Speed
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Hans van Zadelhoff
Submit Date	2015-09-02
Submit Company	Grimme Landmaschinenfabrik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-09-02
Status Comments	

<b>DD Entity</b>	<b>399 - Maximum Speed</b>
Definition	The maximum speed that can be specified in a process data variable for communication between farm management information systems and mobile implement control systems. A positive value will represent forward direction and a negative value will represent reverse direction.
Comment	This DDI has been added to the data dictionary to support the setting and logging of a maximum speed for a part of a device. See also the definitions of the Setpoint, Actual and Minimum Speed DDIs for additional definition and implementation information of Speed DDIs.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops
Unit Symbol	mm/s - Speed
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Hans van Zadelhoff
Submit Date	2015-09-02
Submit Company	Grimme Landmaschinenfabrik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-09-02
Status Comments	

<b>DD Entity</b>	<b>400 - Speed Source</b>
------------------	---------------------------

Definition	<p>The Speed Source that the device uses to report actual speed and to process the setpoint, minimum and maximum speeds. The Speed Source value is an enumeration with the following definitions:</p> <ul style="list-style-type: none"> <li>0 = Unknown</li> <li>1 = Wheel-based speed</li> <li>2 = Ground-based speed</li> <li>3 = Navigation-based speed</li> <li>4 = Blended speed</li> <li>5 = Simulated speed</li> <li>6 = Machine Selected speed</li> <li>7 = Machine measured speed (This option indicates the machine uses an own sensor to measures the actual speed, instead of the speed provided on the bus).</li> <li>8 to 100 = Reserved</li> </ul>
Comment	<p>The Speed Source DDI can be used in conjunction with the Actual Speed DDI to specify which speed measurement method is used to determine the value reported via the Actual, Setpoint, Minimum and Maximum Speed DDIs. When a device receives commands for Setpoint, Minimum or Maximum Speed then the Speed Source can be used to select a ISO 11783-7 command for speed control.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxillary Units</li> <li>14 - Special Crops</li> </ul>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 100
Display Range	0 - 100
Submit by	Jaap van Bergeijk
Submit Date	2015-09-02
Submit Company	AGCO corporation
Revision Number	1
Current Status	ISO-Published
Status Date	2015-09-02
Status Comments	

<b>DD Entity</b>	<b>401 - Actual Application of Nitrogen</b>
Definition	Actual application of Nitrogen [N2] specified as milligram per liter [mg/l]
Comment	Is the actual amount of Nitrogen [N2] in liquid manure ( see also DD Entity 353 )
Typically used by Device Class(es)	5 - Fertilizer
Unit Symbol	mg/l - Mass per capacity unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Christoph Staub
Submit Date	2015-09-02
Submit Company	Zunhammer GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-03-11
Status Comments	

<b>DD Entity</b>	<b>402 - Actual application of Ammonium</b>
Definition	Actual application of Ammonium [NH4] specified as milligram per liter [mg/l]
Comment	Is the actual amount of Ammonium [NH4] in liquig manure ( see also DD Entity 354 )
Typically used by Device Class(es)	5 - Fertilizer
Unit Symbol	mg/l - Mass per capacity unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Christoph Staub
Submit Date	2015-09-02
Submit Company	Zunhammer GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-03-11
Status Comments	



<b>DD Entity</b>	<b>403 - Actual application of Phosphor</b>
Definition	Actual application of Phosphor [P2O5] specified as milligram per liter [mg/l]
Comment	Is the actual amount of Phosphor [P2O5] in liquid manure ( see also DD Entity 355 )
Typically used by Device Class(es)	5 - Fertilizer
Unit Symbol	mg/l - Mass per capacity unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Christoph Staub
Submit Date	2015-03-11
Submit Company	Zunhammer GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>404 - Actual application of Potassium</b>
Definition	Actual application of Potassium [K2] specified as gram [g]
Comment	is the actual amount of Potassium [K2] in liquid manure ( see also DD Entity 356 )
Typically used by Device Class(es)	5 - Fertilizer
Unit Symbol	mg/l - Mass per capacity unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Christoph Staub
Submit Date	2015-09-02
Submit Company	Zunhammer GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-09-04
Status Comments	

<b>DD Entity</b>	<b>405 - Actual application of Dry Matter</b>
Definition	Actual application of Dry Matter in kilogram [kg]. Dry matter measured at Zero percent of moisture.
Comment	is the actual amount of Dry matter in liquid manure ( see also DD Entity 357 )
Typically used by Device Class(es)	5 - Fertilizer
Unit Symbol	mg/l - Mass per capacity unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Christoph Staub
Submit Date	2015-09-02
Submit Company	Zunhammer GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-09-04
Status Comments	

<b>DD Entity</b>	<b>406 - Actual Protein Content</b>
Definition	Actual Protein content of a harvested crops
Comment	Protein content of harvested crop expressed as a percent mass of the total crop.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Joe Tevis
Submit Date	2015-09-04
Submit Company	Topcon
Revision Number	1
Current Status	ISO-Published
Status Date	2015-09-04
Status Comments	

<b>DD Entity</b>	<b>407 - Average Protein Content</b>
Definition	Average protein content in a harvested crop
Comment	Average protein content of harvested crop.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Joe Tevis
Submit Date	2015-09-04
Submit Company	Topcon
Revision Number	1
Current Status	ISO-Published
Status Date	2015-09-04
Status Comments	

<b>DD Entity</b>	<b>408 - Average Crop Contamination</b>
Definition	Average amount of dirt or foreign in a harvested crop
Comment	Average amount of dirt or foreign in a harvested crop
Typically used by Device Class(es)	7 - Harvesters
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Ben Craker
Submit Date	2015-09-02
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-15
Status Comments	

<b>DD Entity</b>	<b>409 - Total Diesel Exhaust Fluid Consumption</b>
Definition	Accumulated Diesel Exhaust Fluid Consumption as a Task Total.
Comment	This data definition is the Diesel Exhaust Fluid (DEF) consumption counterpart of the previously defined data dictionary entity 148 - Total Fuel Consumption. These data dictionary entities can be used by devices that support data logging of Fuel and Diesel Exhaust Fluid consumption.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Eric Bongaerts
Submit Date	2015-06-01
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	
Attachment	<a href="#">2015-06-01: - DEF DDI Requests-v1.pptx</a>

<b>DD Entity</b>	<b>410 - Instantaneous Diesel Exhaust Fluid Consumption per Time</b>
Definition	Diesel Exhaust Fluid consumption per time
Comment	This data definition is the Diesel Exhaust Fluid (DEF) consumption counterpart of the previously defined data dictionary entity 149 - Instantaneous Fuel Consumption per Time. These data dictionary entities can be used by devices that support data logging of Fuel and Diesel Exhaust Fluid consumption.

Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	mm <sup>3</sup> /s - Flow
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Eric Bongaerts
Submit Date	2015-06-01
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	

<b>DD Entity</b>	<b>411 - Instantaneous Diesel Exhaust Fluid Consumption per Area</b>
Definition	Diesel Exhaust Fluid consumption per area
Comment	This data definition is the Diesel Exhaust Fluid (DEF) consumption counterpart of the previously defined data dictionary entity 150 - Instantaneous Fuel Consumption per Area. These data dictionary entities can be used by devices that support data logging of Fuel and Diesel Exhaust Fluid consumption.
Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	mm <sup>3</sup> /m <sup>2</sup> - Capacity per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Eric Bongaerts
Submit Date	2015-06-01
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	

<b>DD Entity</b>	<b>412 - Lifetime Diesel Exhaust Fluid Consumption</b>
Definition	Accumulated Diesel Exhaust Fluid Consumption over the entire lifetime of the device.

Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value.</p> <p>The Device shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p> <p>This data definition is the Diesel Exhaust Fluid (DEF) consumption counterpart of the previously defined data dictionary entity 276 - Lifetime Fuel Consumption. These data dictionary entities can be used by devices that support data logging of Fuel and Diesel Exhaust Fluid consumption.</p>
Typically used by Device Class(es)	<p>1 - Tractor  2 - Primary Soil Tillage  3 - Secondary Soil Tillage  4 - Planters /Seeders  5 - Fertilizer  6 - Sprayers  7 - Harvesters  8 - Root Harvester  9 - Forage harvester  10 - Irrigation  11 - Transport / Trailers  12 - Farmyard Work  13 - Powered Auxiliary Units  14 - Special Crops  15 - Municipal Work  24 - Utility Vehicles  25 - Slurry Applicators  26 - Feeder / Mixer</p>
Unit Symbol	L - Capacity count
Resolution	0,5
SAE SPN	5963
CANBus Range	0 - 2147483647
Display Range	0 - 1073741823,5
Submit by	Eric Bongaerts
Submit Date	2015-06-01
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	

<b>DD Entity</b>	<b>413 - Lifetime Average Diesel Exhaust Fluid Consumption per Time</b>
Definition	Average Diesel Exhaust Fluid Consumption per Time over the entire lifetime of the device.
Comment	<p>This is the overall average of the device. This average does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Device shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p> <p>This data definition is the Diesel Exhaust Fluid (DEF) consumption counterpart of the previously defined data dictionary entity 277 - Lifetime Average Fuel Consumption per Time. These data dictionary entities can be used by devices that support data logging of Fuel and Diesel Exhaust Fluid consumption.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxillary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	mm <sup>3</sup> /s - Flow
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Eric Bongaerts
Submit Date	2015-06-01
Submit Company	AGCO
Revision Number	1



Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	Status was published

<b>DD Entity</b>	<b>414 - Lifetime Average Diesel Exhaust Fluid Consumption per Area</b>
Definition	Average Diesel Exhaust Fluid Consumption per Area over the entire lifetime of the device.
Comment	<p>This is the overall average of the device. This average does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be settable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Device shall support the total trigger method for this DDE but shall not support the settable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p> <p>This data definition is the Diesel Exhaust Fluid (DEF) consumption counterpart of the previously defined data dictionary entity 278 - Lifetime Average Fuel Consumption per Area. These data dictionary entities can be used by devices that support data logging of Fuel and Diesel Exhaust Fluid consumption.</p>
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	mm <sup>3</sup> /m <sup>2</sup> - Capacity per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647

Display Range	0 - 2147483647
Submit by	Eric Bongaerts
Submit Date	2015-06-01
Submit Company	AGCO
Revision Number	1
Current Status	ISO-Published
Status Date	2015-06-16
Status Comments	

<b>DD Entity</b>	<b>415 - Actual Seed Singulation Percentage</b>
Definition	Actual Seed Singulation Percentage calculated from measured seed spacing using ISO 7256-1 "Quality of Feed Index" algorithm
Comment	Reference ISO 7256-1 "Quality of Feed Index" for details on the standardized method for calculating the seed singulation parameter. The number of seed drops for calculating this real-time percentage is not specified due to the possible differences in measurement and performance of the equipment and seeding rates.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	2
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>416 - Average Seed Singulation Percentage</b>
Definition	Average Seed Singulation Percentage calculated from measured seed spacing using ISO 7256-1 "Quality of Feed Index" algorithm. The value is the average for a Task.
Comment	Reference ISO 7256-1 "Quality of Feed Index" for details on the standardized method for calculating the seed singulation parameter. The number of seed drops for calculating this real-time percentage is not specified due to the possible differences in measurement and performance of the equipment and seeding rates.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	2
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>417 - Actual Seed Skip Percentage</b>
Definition	Actual Seed Skip Percentage calculated from measured seed spacing using ISO 7256-1 "Miss Index" algorithm
Comment	Reference ISO 7256-1 "Miss Index" for details on the standardized method for calculating a percentage. The number of seed drops for calculating this real-time percentage is not specified due to the possible differences in measurement and performance of the equipment and seeding rates.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	2
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>418 - Average Seed Skip Percentage</b>
Definition	Average Seed Skip Percentage calculated from measured seed spacing using ISO 7256-1 "Miss Index" algorithm. The value is the average for a Task.
Comment	Reference ISO 7256-1 "Miss Index" for details on the standardized method for calculating a percentage. The number of seed drops for calculating this real-time percentage is not specified due to the possible differences in measurement and performance of the equipment and seeding rates.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	3
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>419 - Actual Seed Multiple Percentage</b>
Definition	Actual Seed Multiple Percentage calculated from measured seed spacing using ISO 7256-1 "Multiples Index" algorithm.
Comment	Reference ISO 7256-1 "Multiples Index" for details on the standardized method for calculating a percentage. The number of seed drops for calculating this real-time percentage is not specified due to the possible differences in measurement and performance of the equipment and seeding rates.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	3
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>420 - Average Seed Multiple Percentage</b>
Definition	Average Seed Multiple Percentage calculated from measured seed spacing using ISO 7256-1 "Multiples Index" algorithm. The value is the average for a Task.
Comment	Reference ISO 7256-1 "Multiples Index" for details on the standardized method for calculating a percentage. The number of seed drops for calculating this real-time percentage is not specified due to the possible differences in measurement and performance of the equipment and seeding rates.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	3
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>421 - Actual Seed Spacing Deviation</b>
Definition	Actual Seed Spacing Deviation from setpoint seed spacing
Comment	Deviation is a positive value independently of if distance between seeds is smaller or larger than the setpoint value
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	3
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>422 - Average Seed Spacing Deviation</b>
Definition	Average Seed Spacing Deviation from setpoint seed spacing. The value is the average for a Task.
Comment	Deviation is a positive value independently of if distance between seeds is smaller or larger than the setpoint value
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	3
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>423 - Actual Coefficient of Variation of Seed Spacing Percentage</b>
Definition	Actual Coefficient of Variation of Seed Spacing Percentage calculated from measured seed spacing using ISO 7256-1 algorithm
Comment	Reference ISO 7256-1 "Coefficient of Variation" for details on the standardized method for calculating a percentage. The number of seed drops for calculating this real-time percentage is not specified due to the possible differences in measurement and performance of the equipment and seeding rates.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	3
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>424 - Average Coefficient of Variation of Seed Spacing Percentage</b>
Definition	Average Coefficient of Variation of Seed Spacing Percentage calculated from measured seed spacing using ISO 7256-1 algorithm. The value is the average for a Task.
Comment	Reference ISO 7256-1 "Coefficient of Variation" for details on the standardized method for calculating a percentage. The number of seed drops for calculating this real-time percentage is not specified due to the possible differences in measurement and performance of the equipment and seeding rates.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 1000000
Display Range	0 - 1000000
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	5
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>425 - Setpoint Maximum Allowed Seed Spacing Deviation</b>
Definition	Setpoint Maximum Allowed Seed Spacing Deviation
Comment	Value is for TIM purposes. An acceptable seeding quality range can be defined in a task or prescription. Deviation is a positive value independently of if distance between seeds is smaller or larger than the setpoint value
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Matthias Rothmund
Submit Date	2015-03-25
Submit Company	HORSCH
Revision Number	5
Current Status	ISO-Submitted (Pending)
Status Date	2015-07-30
Status Comments	

<b>DD Entity</b>	<b>426 - Setpoint Downforce as Force</b>
Definition	Setpoint Downforce as Force
Comment	This value represents the system pressure to produce the downforce (or upforce) for an operation measured in newton; In case of an negative value the system pressure would produce Upforce.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	N - Newton
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Rothmund
Submit Date	2015-09-03
Submit Company	HORSCH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-09-03
Status Comments	



<b>DD Entity</b>	<b>427 - Actual Downforce as Force</b>
Definition	Actual Downforce as Force
Comment	This value represents the actual downforce to produce the downforce (or upforce) for an operation measured in newton; In case of an negative value the system pressure would produce Upforce.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	N - Newton
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Matthias Rothmund
Submit Date	2015-09-03
Submit Company	HORSCH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-09-03
Status Comments	

<b>DD Entity</b>	<b>428 - Loaded Total Mass</b>
Definition	Accumulated Loads specified as mass, not corrected for the reference moisture percentage DDI 184.
Comment	Is a counter of a machine element.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-02
Status Comments	

<b>DD Entity</b>	<b>429 - Unloaded Total Mass</b>
Definition	Accumulated Unloads specified as mass, not corrected for the reference moisture percentage DDI 184.
Comment	Is a counter of a machine element.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-02
Status Comments	

<b>DD Entity</b>	<b>430 - Lifetime Loaded Total Mass</b>
Definition	Entire Yield Total Mass of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	

CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-02
Status Comments	

<b>DD Entity</b>	<b>431 - Lifetime Unloaded Total Mass</b>
Definition	Entire Unloaded Total Mass of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<p>4 - Planters /Seeders</p> <p>5 - Fertilizer</p> <p>7 - Harvesters</p> <p>8 - Root Harvester</p> <p>9 - Forage harvester</p> <p>11 - Transport / Trailers</p> <p>17 - Sensor System</p>
Unit Symbol	kg - Mass
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-02
Status Comments	

<b>DD Entity</b>	<b>432 - Setpoint Application Rate of Nitrogen</b>
Definition	Setpoint application rate of nitrogen specified as a mass per area
Comment	As a reference the total amount of nitrogen will be documented with DDE353
Typically used by Device Class(es)	<p>4 - Planters /Seeders</p> <p>5 - Fertilizer</p> <p>6 - Sprayers</p> <p>17 - Sensor System</p> <p>25 - Slurry Applicators</p>
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295

Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>433 - Actual Application Rate of Nitrogen</b>
Definition	Actual application rate of nitrogen specified as a mass per area
Comment	As a reference the total amount of nitrogen will be documented with DDE353
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>434 - Minimum Application Rate of Nitrogen</b>
Definition	Minimum application rate of nitrogen specified as a mass per area
Comment	As a reference the total amount of nitrogen will be documented with DDE353
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>435 - Maximum Application Rate of Nitrogen</b>
Definition	Maximum application rate of nitrogen specified as a mass per area
Comment	As a reference the total amount of nitrogen will be documented with DDE353
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>436 - Setpoint Application Rate of Ammonium</b>
Definition	Setpoint application rate of Ammonium specified as a mass per area
Comment	As a reference the total amount of ammonium will be documented with DDE354
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>437 - Actual Application Rate of Ammonium</b>
Definition	Actual application rate of Ammonium specified as a mass per area
Comment	As a reference the total amount of Ammonium will be documented with DDE354
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>438 - Minimum Application Rate of Ammonium</b>
Definition	Minimum application rate of Ammonium specified as a mass per area
Comment	As a reference the total amount of ammonium will be documented with DDE354
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	



<b>DD Entity</b>	<b>439 - Maximum Application Rate of Ammonium</b>
Definition	Maximum application rate of Ammonium specified as a mass per area
Comment	As a reference the total amount of ammonium will be documented with DDE354
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>440 - Setpoint Application Rate of Phosphor</b>
Definition	Setpoint application rate of phosphor specified as a mass per area
Comment	As a reference the total amount of phosphor will be documented with DDE355
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>441 - Actual Application Rate of Phosphor</b>
Definition	Actual application rate of phosphor specified as a mass per area
Comment	As a reference the total amount of phosphor will be documented with DDE355
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>442 - Minimum Application Rate of Phosphor</b>
Definition	Minimum application rate of phosphor specified as a mass per area
Comment	As a reference the total amount of phosphor will be documented with DDE355
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>443 - Maximum Application Rate of Phosphor</b>
Definition	Maximum application rate of phosphor specified as a mass per area
Comment	As a reference the total amount of phosphor will be documented with DDE355
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH & Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>444 - Setpoint Application Rate of Potassium</b>
Definition	Setpoint application rate of potassium specified as a mass per area
Comment	As a reference the total amount of potassium will be documented with DDE356
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-02
Status Comments	

<b>DD Entity</b>	<b>445 - Actual Application Rate of Potassium</b>
Definition	Actual application rate of potassium specified as a mass per area
Comment	As a reference the total amount of potassium will be documented with DDE356
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Jan Steenbock
Submit Date	2015-11-02
Submit Company	Müller-Elektronik GmbH Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>446 - Minimum Application Rate of Potassium</b>
Definition	Minimum application rate of potassium specified as a mass per area
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jan Steenbock
Submit Date	2016-03-29
Submit Company	Müller-Elektronik GmbH Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>447 - Maximum Application Rate of Potassium</b>
Definition	Maximum application rate of potassium specified as a mass per area
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mg/m <sup>2</sup> - Mass per area unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jan Steenbock
Submit Date	2015-11-03
Submit Company	Müller-Elektronik GmbH Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>448 - Setpoint Application Rate of Dry Matter</b>
Definition	Setpoint application rate of dry matter expressed as percentage
Comment	As a reference the total amount of dry matter will be documented with DDE 357
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	ppm (parts per million) - Quantity per quantity unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jan Steebock
Submit Date	2015-11-03
Submit Company	Müller-Elektronik GmbH Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>449 - Actual Application Rate of Dry Matter</b>
Definition	Actual application rate of dry matter expressed as percentage
Comment	As a reference the total amount of dry matter will be documented with DDE 357
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	ppm (parts per million) - Quantity per quantity unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jan Steenbock
Submit Date	2015-09-03
Submit Company	Müller-Elektronik GmbH Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>450 - Minimum Application Rate of Dry Matter</b>
Definition	Minimum application rate of dry matter expressed as percentage
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	ppm (parts per million) - Quantity per quantity unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jan Steenbock
Submit Date	2015-11-03
Submit Company	Müller-Elektronik GmbH Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>451 - Maximum Application Rate of Dry Matter</b>
Definition	Maximum application rate of dry matter expressed as percentage
Comment	
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	ppm (parts per million) - Quantity per quantity unit
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Jan Steenbock
Submit Date	2015-11-03
Submit Company	Müller-Elektronik GmbH Co. KG
Revision Number	1
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>452 - Loaded Total Volume</b>
Definition	Accumulated Loaded Volume specified as volume
Comment	Is a counter of a machine element
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>453 - Unloaded Total Volume</b>
Definition	Accumulated Unloaded Volume specified as volume
Comment	Is a counter of a machine element
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>454 - Lifetime loaded Total Volume</b>
Definition	Entire loaded Volume of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 17 - Sensor System



Unit Symbol	L - Capacity count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>455 - Lifetime Unloaded Total Volume</b>
Definition	Entire unloaded Volume of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<p>4 - Planters /Seeders</p> <p>5 - Fertilizer</p> <p>6 - Sprayers</p> <p>7 - Harvesters</p> <p>8 - Root Harvester</p> <p>9 - Forage harvester</p> <p>10 - Irrigation</p> <p>11 - Transport / Trailers</p> <p>17 - Sensor System</p>
Unit Symbol	L - Capacity count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>456 - Last loaded Volume</b>
Definition	Last loaded Volume value specified as volume
Comment	<p>After a loading Procedure, this DDI sends the loaded Volume.</p> <p>For more information see attachment located at Last loaded Weight DDE320</p>

Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>457 - Last unloaded Volume</b>
Definition	Last unloaded Volume value specified as volume
Comment	After a unloading Procedure, this DDI sends the unloaded Volume.  For more information see attachment located at Last loaded Weight DDE320
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>458 - Loaded Total Count</b>
Definition	Accumulated Loads specified as count
Comment	Is a counter of a device element
Typically used by Device Class(es)	4 - Planters /Seeders 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 14 - Special Crops 17 - Sensor System
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2

Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>459 - Unloaded Total Count</b>
Definition	Accumulated Unloaded specified as count
Comment	Is a counter of a device element
Typically used by Device Class(es)	4 - Planters /Seeders 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 14 - Special Crops 17 - Sensor System
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>460 - Lifetime Loaded Total Count</b>
Definition	Entire Loaded Total Count of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	4 - Planters /Seeders 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 14 - Special Crops 17 - Sensor System
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647

Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>461 - Lifetime Unloaded Total Count</b>
Definition	Entire Unloaded Total Count of the device lifetime.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be setable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the setable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<p>4 - Planters /Seeders</p> <p>7 - Harvesters</p> <p>8 - Root Harvester</p> <p>9 - Forage harvester</p> <p>11 - Transport / Trailers</p> <p>14 - Special Crops</p> <p>17 - Sensor System</p>
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>462 - Last loaded Count</b>
Definition	Last loaded Count value specified as count
Comment	<p>After a loading Procedure, this DDI sends the loaded Count.</p> <p>For more information see attachment located at Last loaded Weight DDE320</p>
Typically used by Device Class(es)	<p>4 - Planters /Seeders</p> <p>7 - Harvesters</p> <p>8 - Root Harvester</p> <p>9 - Forage harvester</p> <p>11 - Transport / Trailers</p> <p>17 - Sensor System</p>
Unit Symbol	# - Quantity/Count
Resolution	1



SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>463 - Last unloaded Count</b>
Definition	Last unloaded Count value specified as count
Comment	After a unloading Procedure, this DDI sends the loaded Count.  For more information see attachment located at Last loaded Weight DDE 320
Typically used by Device Class(es)	4 - Planters /Seeders 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 14 - Special Crops 17 - Sensor System
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-11-03
Status Comments	

<b>DD Entity</b>	<b>464 - Haul Counter</b>
Definition	Each Time a Device Element is filled and emptied this is called a haul cycle. This counter counts the cycles
Comment	Is a counter of a device element. Can be used to count loads, fillings, tippings and such.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH

Revision Number	2
Current Status	ISO-Published
Status Date	2015-12-14
Status Comments	

<b>DD Entity</b>	<b>465 - Lifetime Haul Counter</b>
Definition	The number of haul cycles done by a machine over its entire lifetime. This DDE value can not be set through the process data interface but can be requested and added to a datalog. This DDE value is not affected by a task based total haul cycles but will increment at the same rate as the task based total.
Comment	<p>This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be settable within the device description and neither shall the device reset the value when the task status changes. It is up to the device control system when to reset this value.</p> <p>The Working Set Master shall support the total trigger method for this DDE but shall not support the settable property.</p> <p>The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.</p>
Typically used by Device Class(es)	<p>4 - Planters /Seeders</p> <p>5 - Fertilizer</p> <p>6 - Sprayers</p> <p>7 - Harvesters</p> <p>8 - Root Harvester</p> <p>9 - Forage harvester</p> <p>10 - Irrigation</p> <p>11 - Transport / Trailers</p> <p>17 - Sensor System</p>
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Franz Hoepfinger
Submit Date	2015-07-24
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	2
Current Status	ISO-Published
Status Date	2015-12-14
Status Comments	

<b>DD Entity</b>	<b>466 - Actual relative connector angle</b>
------------------	--

Definition	<p>The DDI Actual relative connector angle shall be placed in the device element of type connector in the DDOP of the TC-SC Client. The value describes the actual angle of the longitudinal axis of the implement relative to the longitudinal axis of the tractor. This angle should be used by the TC-SC server to calculate the real position of implement. The TC-SC server may smooth the rendering in any proprietary screen.</p> <p>The reference system is the coordinate system of the tractor. This results in the angles from table 1 of the attachment.</p> <p>In case of for example a malfunction sensor the error value is set to 0xFExxxxxx.</p>
Comment	<p>When working with Section Control it is necessary that the TC-Server calculates the exact position of the implement and its boom and sections to mark the covered area on its section control screen properly. To calculate the positions the TC-SC server uses the x and y offsets of the DRP and CRP. This works well for mounted and for non-steered trailed implements but comes up against limits when implements do have a steering axle or even a steering drawbar because the TC-SC server can't know the current steering angle and moving the DRP doesn't fit in all means. But this could be solved when the TC-SC server would knew the exact angle of the implement related to the tractor. This information could be provided by the implement because when they have a steering mechanism they even have a sensor to measure the angle between tractor and implement.</p>
Typically used by Device Class(es)	<p>2 - Primary Soil Tillage  3 - Secondary Soil Tillage  4 - Planters /Seeders  5 - Fertilizer  6 - Sprayers  25 - Slurry Applicators</p>
Unit Symbol	° - Angle
Resolution	0,001
SAE SPN	
CANBus Range	-180000 - 180000
Display Range	-180,000 - 180,000
Submit by	Thomas Konermann
Submit Date	2015-07-27
Submit Company	AMAZONEN-Werke H. Dreyer GmbH & Co. KG
Revision Number	2
Current Status	ISO-Published
Status Date	2016-01-25
Status Comments	
Attachment	<a href="#">2015-07-27: - Actual relative connector angle-v1.pdf</a>

DD Entity	467 - Actual Percentage Content
Definition	Actual Device Element Content specified as percent.
Comment	
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	% - Percent
Resolution	0,01
SAE SPN	
CANBus Range	0 - 10000
Display Range	0,00 - 100,00
Submit by	Matthias Meyer
Submit Date	2016-06-13
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-13
Status Comments	

DD Entity	472 - Setpoint Length of Cut
Definition	Setpoint length of cut for harvested material, e.g. Forage Harvester or Tree Harvester.
Comment	

Typically used by Device Class(es)	0 - Non-specific system 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483,647
Display Range	0,000 - 2,147,484
Submit by	Frank Wiebeler
Submit Date	2016-03-21
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2016-03-21
Status Comments	

<b>DD Entity</b>	<b>473 - Minimum length of cut</b>
Definition	Minimum length of cut for harvested material, e.g. Forage Harvester or Tree Harvester.
Comment	
Typically used by Device Class(es)	0 - Non-specific system 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483,647
Display Range	0,000 - 2,147,484
Submit by	Frank Wiebeler
Submit Date	2016-03-21
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2016-03-21
Status Comments	

<b>DD Entity</b>	<b>474 - Maximum Length of Cut</b>
Definition	Maximum length of cut for harvested material, e.g. Forage Harvester or Tree Harvester.
Comment	
Typically used by Device Class(es)	0 - Non-specific system 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 14 - Special Crops
Unit Symbol	mm - Length
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483,647
Display Range	0,000 - 2,147,484
Submit by	Frank Wiebeler
Submit Date	2016-03-21
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2016-03-21
Status Comments	



<b>DD Entity</b>	<b>475 - Setpoint Bale Hydraulic Pressure</b>
Definition	The setpoint value of the hydraulic pressure applied to the sides of the bale in the bale compression chamber.
Comment	
Typically used by Device	7 - Harvesters
Class(es)	9 - Forage harvester
Unit Symbol	Pa - Pressure
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2016-03-21
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2016-03-21
Status Comments	

<b>DD Entity</b>	<b>476 - Minimum Bale Hydraulic Pressure</b>
Definition	The minimum value of the hydraulic pressure applied to the sides of the bale in the bale compression chamber.
Comment	
Typically used by Device	7 - Harvesters
Class(es)	9 - Forage harvester
Unit Symbol	Pa - Pressure
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2016-03-21
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2016-03-21
Status Comments	

<b>DD Entity</b>	<b>477 - Maximum Bale Hydraulic Pressure</b>
Definition	The maximum value of the hydraulic pressure applied to the sides of the bale in the bale compression chamber.
Comment	
Typically used by Device	7 - Harvesters
Class(es)	9 - Forage harvester
Unit Symbol	Pa - Pressure
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2016-03-21
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2016-03-21
Status Comments	

<b>DD Entity</b>	<b>478 - Setpoint Flake Size</b>
Definition	Setpoint size of the flake to be produced by the chamber.
Comment	See also DDI 364.
Typically used by Device	7 - Harvesters
Class(es)	9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 1000
Display Range	0 - 1000
Submit by	Frank Wiebeler
Submit Date	2016-03-21
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2016-03-21
Status Comments	

<b>DD Entity</b>	<b>479 - Minimum Flake Size</b>
Definition	Minimum size of the flake that can be produced by the chamber.
Comment	See also DDI 364.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 1000
Display Range	0 - 1000
Submit by	Frank Wiebeler
Submit Date	2016-03-21
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2016-03-21
Status Comments	

<b>DD Entity</b>	<b>480 - Maximum Flake Size</b>
Definition	Maximum size of the flake that can be produced by the chamber.
Comment	See also DDI 364
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 1000
Display Range	0 - 1000
Submit by	Frank Wiebeler
Submit Date	2016-03-21
Submit Company	Maschinenfabrik Bernard Krone GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2016-03-21
Status Comments	

DD Entity	481 - Setpoint Number of Subbales
Definition	Number of smaller bales that shall be included in one bigger bale.
Comment	Defines the number of sub-bales included of a big square bale.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2016-03-09
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-13
Status Comments	

DD Entity	482 - Last Bale Number of Subbales
Definition	Number of smaller bales included in the latest produced bale.
Comment	This DDI is needed as there might be another bale in the chamber. When sending this DDI on dropping the bale on the field, the system can define how many subbales are in that specific bale.
Typically used by Device Class(es)	7 - Harvesters 9 - Forage harvester 11 - Transport / Trailers
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2016-03-09
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-13
Status Comments	

<b>DD Entity</b>	<b>483 - Setpoint Engine Speed</b>
Definition	The setpoint of the rotational speed of the engine.
Comment	The addition of a DDI for such values allows such values to be added to the default data set that devices present to a task controller or a data logger
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	r/min - Revolutions per minute
Resolution	0,0001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,0000 - 214748,3647
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-13
Status Comments	

<b>DD Entity</b>	<b>484 - Actual Engine Speed</b>
Definition	Actual rotational speed of the engine.

Comment	The addition of a DDI for such values allows such values to be added to the default data set that devices present to a task controller or a data logger.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxillary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> <li>18 - Reserved for Future Assignment</li> <li>19 - Timber Harvesters</li> <li>20 - Forwarders</li> <li>21 - Timber loaders</li> <li>22 - Timber Processing Machines</li> <li>23 - Mulchers</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	r/min - Revolutions per minute
Resolution	0,0001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,0000 - 214748,3647
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-13
Status Comments	

<b>DD Entity</b>	<b>485 - Minimum Engine Speed</b>
Definition	The minimum of the rotational speed of the engine.
Comment	The addition of a DDI for such values allows such values to be added to the default data set that devices present to a task controller or a data logger
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	r/min - Revolutions per minute
Resolution	0,0001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,0000 - 214748,3647
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-13
Status Comments	

<b>DD Entity</b>	<b>486 - Maximum Engine Speed</b>
Definition	The maximum of the rotational speed of the engine.

Comment	The addition of a DDI for such values allows such values to be added to the default data set that devices present to a task controller or a data logger.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> <li>18 - Reserved for Future Assignment</li> <li>19 - Timber Harvesters</li> <li>20 - Forwarders</li> <li>21 - Timber loaders</li> <li>22 - Timber Processing Machines</li> <li>23 - Mulchers</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	r/min - Revolutions per minute
Resolution	0,0001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,0000 - 214748,3647
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-13
Status Comments	



<b>DD Entity</b>	<b>488 - Diesel Exhaust Fluid Tank Percentage Level</b>
Definition	The actual level of the Diesel Exhaust Fluid Tank in percent.
Comment	The addition of a percentage DDI allows such values to be added to the default data set that devices present to a task controller or a data logger
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> <li>18 - Reserved for Future Assignment</li> <li>19 - Timber Harvesters</li> <li>20 - Forwarders</li> <li>21 - Timber loaders</li> <li>22 - Timber Processing Machines</li> <li>23 - Mulchers</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	% - Percent
Resolution	0,01
SAE SPN	
CANBus Range	0 - 10000
Display Range	0,00 - 100,00
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-13
Status Comments	

<b>DD Entity</b>	<b>489 - Maximum Diesel Exhaust Fluid Tank Content</b>
------------------	--

Definition	This value describes the maximum amount of Diesel Exhaust fluid, that can be filled into the tank of the machine
Comment	
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxilary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> <li>18 - Reserved for Future Assignment</li> <li>19 - Timber Harvesters</li> <li>20 - Forwarders</li> <li>21 - Timber loaders</li> <li>22 - Timber Processing Machines</li> <li>23 - Mulchers</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-13
Status Comments	

<b>DD Entity</b>	<b>490 - Maximum Fuel Tank Content</b>
Definition	This value describes the maximum amount of fuel that can be filled into the machines Fuel tank.
Comment	
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> <li>18 - Reserved for Future Assignment</li> <li>19 - Timber Harvesters</li> <li>20 - Forwarders</li> <li>21 - Timber loaders</li> <li>22 - Timber Processing Machines</li> <li>23 - Mulchers</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	ml - Capacity large
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-14
Status Comments	

<b>DD Entity</b>	<b>491 - Fuel Percentage Level</b>
Definition	The actual level of the machine fuel tank in percent.
Comment	

Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> <li>18 - Reserved for Future Assignment</li> <li>19 - Timber Harvesters</li> <li>20 - Forwarders</li> <li>21 - Timber loaders</li> <li>22 - Timber Processing Machines</li> <li>23 - Mulchers</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	% - Percent
Resolution	0,01
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,00 - 21474836,47
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-14
Status Comments	

<b>DD Entity</b>	<b>492 - Total Engine Hours</b>
Definition	The total time the engine was running when the task was active.
Comment	
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxilary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> <li>18 - Reserved for Future Assignment</li> <li>19 - Timber Harvesters</li> <li>20 - Forwarders</li> <li>21 - Timber loaders</li> <li>22 - Timber Processing Machines</li> <li>23 - Mulchers</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	h - Hour
Resolution	0,05
SAE SPN	
CANBus Range	0 - 210554060,75
Display Range	0,0 - 10527703,038
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-14
Status Comments	

<b>DD Entity</b>	<b>493 - Lifetime Engine Hours</b>
Definition	The total time, when the engine was running over the whole lifetime of the machine.
Comment	

Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	h - Hour
Resolution	0,1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 214748364,7
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	
Status Date	2016-04-01
Status Comments	

<b>DD Entity</b>	<b>494 - Last Event Partner ID (Byte 1-4)</b>
Definition	Last Event Partner ID as a decimal number of 128bit length.  This DDI should include the Byte 1-4 of the Last Event Partner ID. It should always be sent as Group of 4 DDI's to send all 128 bit together. After this a DDI 147 "Log Count" shall be sent.
Comment	Using Methods do determine the Location of a Vehicle or Storage which is not equipped with ISOBUS and GPS.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0 - 0xFFFFFFFF
Display Range	0 - 0xFFFFFFFF
Submit by	Franz Hoepfinger
Submit Date	2016-07-20
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	1
Current Status	ISO-Published
Status Date	2015-10-11
Status Comments	
Attachment	<a href="#">2016-07-20: - ISO11783-11-DDI-494 Partner ID-v1.pdf</a>

<b>DD Entity</b>	<b>495 - Last Event Partner ID (Byte 5-8)</b>
Definition	Last Event Partner ID as a decimal number of 128bit length.  This DDI should include the Byte 5-8 of the Last Event Partner ID. It should always be sent as Group of 4 DDI's to send all 128 bit together. After this a DDI 147 "Log Count" shall be sent.
Comment	Using Methods do determine the Location of a Vehicle or Storage which is not equipped with ISOBUS and GPS. See also DDI 494 attachment.

Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0x00000000 - 0xFFFFFFFF
Display Range	0x00000000 - 0xFFFFFFFF
Submit by	Franz Hoepfinger
Submit Date	2015-10-11
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	3
Current Status	ISO-Published
Status Date	2016-06-15
Status Comments	



<b>DD Entity</b>	<b>496 - Last Event Partner ID (Byte 9-12)</b>
Definition	Last Event Partner ID as a decimal number of 128bit length.  This DDI should include the Byte 9-12 of the Last Event Partner ID. It should always be sent as Group of 4 DDI's to send all 128 bit together. After this a DDI 147 "Log Count" shall be sent.
Comment	Using Methods do determine the Location of a Vehicle or Storage which is not equipped with ISOBUS and GPS. See also DDI 494 attachment.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0x00000000 - 0xFFFFFFFF
Display Range	0x00000000 - 0xFFFFFFFF
Submit by	Franz Hoepfinger
Submit Date	2015-10-11
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	3
Current Status	ISO-Published
Status Date	2016-06-15
Status Comments	

<b>DD Entity</b>	<b>497 - Last Event Partner ID (Byte 13-16)</b>
Definition	Last Event Partner ID as a decimal number of 128bit length.  This DDI should include the Byte 13-16 of the Last Event Partner ID. It should always be sent as Group of 4 DDI's to send all 128 bit together. After this a DDI 147 "Log Count" shall be sent.
Comment	Using Methods do determine the Location of a Vehicle or Storage which is not equipped with ISOBUS and GPS. See also DDI 494 attachment.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System

Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0x00000000 - 0xFFFFFFFF
Display Range	0x00000000 - 0xFFFFFFFF
Submit by	Franz Hoepfinger
Submit Date	2015-10-11
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	3
Current Status	ISO-Published
Status Date	2016-06-15
Status Comments	

<b>DD Entity</b>	<b>498 - Last Event Partner ID Type</b>
Definition	Defines The Type of the Partner ID Device. See Attachment for Definition.
Comment	See also DDI 494 attachment.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0x00000000 - 0xFFFFFFFF
Display Range	0x00000000 - 0xFFFFFFFF
Submit by	Franz Hoepfinger
Submit Date	2015-10-11
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	4
Current Status	ISO-Published
Status Date	2016-06-20
Status Comments	Status was published

<b>DD Entity</b>	<b>499 - Last Event Partner ID Manufacturer ID Code</b>
Definition	The Partner ID has to tell its Manufacturer, and the Manufacturer Numbers from SAE J1939 / ISO 11783 shall be used.
Comment	Remark: This is not the Manufacturer of the ISOBUS ECU sending this DDI to the Task-Controller, but the Manufacturer of the "Partner" Device. See also DDI 494 attachment.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	not defined - not defined
Resolution	1
SAE SPN	
CANBus Range	0x00000000 - 0xFFFFFFFF
Display Range	0x00000000 - 0xFFFFFFFF
Submit by	Franz Hoepfinger

Submit Date	2015-10-11
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	4
Current Status	ISO-Published
Status Date	2016-06-20
Status Comments	Status was published

<b>DD Entity</b>	<b>500 - Last Event Partner ID Device Class</b>
Definition	This DDI should tell the Device Class of the "Partner" Device.
Comment	Look at DDI 494 attachment to get the device class details.
Typically used by Device Class(es)	4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 11 - Transport / Trailers 17 - Sensor System
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0x00000000 - 0xFFFFFFFF
Display Range	0x00000000 - 0xFFFFFFFF
Submit by	Franz Hoepfinger
Submit Date	2015-10-11
Submit Company	367 - Fliegl Agrartechnik GmbH
Revision Number	4
Current Status	ISO-Published
Status Date	2016-06-20
Status Comments	Status was published

<b>DD Entity</b>	<b>501 - Setpoint Engine Torque</b>
Definition	The setpoint of the engine torque.
Comment	The addition of a DDI for such values allows such values to be added to the default data set that devices present to a task controller or a data logger.

Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> <li>18 - Reserved for Future Assignment</li> <li>19 - Timber Harvesters</li> <li>20 - Forwarders</li> <li>21 - Timber loaders</li> <li>22 - Timber Processing Machines</li> <li>23 - Mulchers</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	% - Percent
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	5
Current Status	ISO-Published
Status Date	2016-06-28
Status Comments	

<b>DD Entity</b>	<b>502 - Actual Engine Torque</b>
Definition	The current torque of the engine.
Comment	The addition of a DDI for such values allows such values to be added to the default data set that devices present to a task controller or a data logger
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> <li>18 - Reserved for Future Assignment</li> <li>19 - Timber Harvesters</li> <li>20 - Forwarders</li> <li>21 - Timber loaders</li> <li>22 - Timber Processing Machines</li> <li>23 - Mulchers</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	% - Percent
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0,000 - 2,147,483,647
Submit by	
Submit Date	2016-04-01
Submit Company	
Revision Number	2
Current Status	ISO-Published
Status Date	2016-06-28
Status Comments	

<b>DD Entity</b>	<b>503 - Minimum Engine Torque</b>
Definition	The minimum value of the engine torque

Comment	
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	% - Percent
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483,647
Submit by	Frank Wiebeler
Submit Date	2016-06-28
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-28
Status Comments	



<b>DD Entity</b>	<b>504 - Maximum Engine Torque</b>
Definition	The maximum value of the engine torque
Comment	
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxillary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	% - Percent
Resolution	0,001
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483,647
Submit by	Frank Wiebeler
Submit Date	2016-06-28
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-06-28
Status Comments	

<b>DD Entity</b>	<b>505 - Tramline Control Level</b>
Definition	This DDI defines the Tramline Control capability of the Implement.

Comment	<p>The Implement shall provide in its root DeviceElement which Tramline Control Levels are supported. The Tramline Control Levels are independent of each other. It is allowed to support for example only Level 3 Tramlining.</p> <p>Byte 1 Bit 0 = 1 Support Tramline Control Level 1          Byte 1 Bit 1 = 1 Support Tramline Control Level 2          Byte 1 Bit 2 = 1 Support Tramline Control Level 3          Byte 1 Bit 3-7 = 0 Reserved</p>
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 7
Display Range	0 - 7
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	3
Current Status	ISO-Published
Status Date	2016-08-24
Status Comments	
Attachment	<a href="#">2017-01-25: - TramlineControl_BasicRequirements_v1.12-v2.pdf</a>

<b>DD Entity</b>	<b>506 - Setpoint Tramline Control Level</b>
Definition	This DDI defines the Tramline Control capability of the Task Controller that is used with the appropriate Implement.
Comment	<p>The Task Controller shall send this value to inform the Implement which Tramline Control Level shall be used to operate. In case there is no match between the supported Tramline Control Level on the Task Controller Server side and the Implement, the Task Controller shall inform the Implement by setting the Setpoint Tramline Control Level to 0.</p> <p>This is the response to the Tramline Control Level DDI.</p> <p>0 No common Level  1 Tramline Control Level 1  2 Tramline Control Level 2  3 Tramline Control Level 3  4-255 Reserved for future Assignment</p> <p>For more details see also attachment on DDI 505.</p>
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>507 - Tramline Sequence Number</b>
Definition	This DDI defines a group of DDIs which belong together.

Comment	<p>In order to ensure that the parameters "Unique A-B Guidance Reference Line ID", "Actual Track Number", "Track Number to the right" and "Track Number the left" are belonging together, the Tramline Sequence Number is needed. This parameter has to be sent from the Tramline Controller to indicate a new Tramline Sequence to the Implement. This number shall start with value 1 and increase on every new Tramline Sequence which is going to be sent. These Parameters are only allowed to be sent in a group, except the Unique A-B Guidance Reference Line ID. If one of the parameters is missing, the Tramline Sequence would be invalid. In case the Unique A-B Guidance Reference Line ID shall be part of the Tramline Sequence, this value shall be sent as first value after the Tramline Sequence Number and before other values.</p> <p>It is recommended to send all values belonging to one Tramline Sequence within 500 ms.</p> <p>For more details see also attachment on DDI 505.</p>
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>508 - Unique A-B Guidance Reference Line ID</b>
Definition	This DDI defines a unique ID to identify which Guidance Reference Line is the base for the Tramline calculation.
Comment	A field could have more than one Guidance Reference Line. For example the field could have a Guidance Reference Line for the headland and also another Guidance Reference Line for the main field. To distinguish between the several Guidance Reference Lines a Guidance Reference Line ID is used. This unique ID identifies which Guidance Reference Line is the base for the Tramline calculation.  For more details see also attachment on DDI 505.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>509 - Actual Track Number</b>
Definition	This DDI defines a unique number of the Guidance Track the Implement is currently located on.
Comment	The Actual Track Number is the unique Number of the Guidance Track the Implement is currently located on. This number is provided by the Guidance System.  For more details see also attachment on DDI 505.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01

Status Comments	
-----------------	--

<b>DD Entity</b>	<b>510 - Track Number to the right</b>
Definition	This DDI defines a unique number of the Guidance Track to right hand side in direction of Implement orientation.
Comment	This is the Guidance Track Number to right hand side in direction of Implement orientation. If the Track Number to the right is higher than the Actual Track Number, then the Implement is in the same direction as the A-B reference line. The Implement orientation is independent of the driving direction of the Implement. This value is provided by the Guidance System.  For more details see also attachment on DDI 505.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>511 - Track Number to the left</b>
Definition	This DDI defines a unique number of the Guidance Track to left hand side in direction of Implement orientation.
Comment	This is the Guidance Track Number to left hand side in direction of Implement orientation  This value may be used in addition to the Track Number to the right for differentiating between the two Guidance Track 0 Numbers (0R and 0L). This value is needed, because there are two cases where the Actual Track Number and the Track Number to the right are both 0. This value is provided by the Guidance System.  For more details see also attachment on DDI 505.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Karsten Helweg
Submit Date	2015-12-10

Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	



<b>DD Entity</b>	<b>512 - Guidance Line Swath Width</b>
Definition	The Swath Width is the Distance between two adjacent Guidance Lines in a Guidance Pattern.
Comment	The User may prefer to choose a distance between two adjacent Guidance Lines which is a little smaller or bigger than the Seeder Working Width. The Implement may use this information to apply correction on its Tramline calculation.  For more details see also attachment on DDI 505.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>513 - Guidance Line Deviation</b>
Definition	Deviation of the Device-Reference-Point (DRP) to the actual guidance line, in driving direction.
Comment	This DDI shall be sent from the Guidance System or Task Controller. It specifies the Deviation in mm between the current Guidance Line and the Device Reference Point which is guided along the Guidance Line.  The Guidance Line Deviation is positive when the Guidance Line is located on the right hand side of the Device Reference Point in driving direction.  The Guidance Line Deviation is negative when the Guidance Line is located on the left hand side of Device Reference Point in driving direction.  For more details see also attachment on DDI 505.

Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 17 - Sensor System 25 - Slurry Applicators
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>514 - GNSS Quality</b>
Definition	GNSS Quality Identifier to inform the implement about the used Position Status.
Comment	<p>This DDI shall be sent from the Guidance System or Task Controller to the implement. It specifies the quality of the GNSS which is used by the Guidance System or Task Controller.</p> <p>Definition references NMEA2000 Method GNSS parameter as also mentioned in ISO11783-10.</p> <p>For more details see also attachment on DDI 505.</p>
Typically used by Device Class(es)	<p>1 - Tractor</p> <p>2 - Primary Soil Tillage</p> <p>3 - Secondary Soil Tillage</p> <p>4 - Planters /Seeders</p> <p>5 - Fertilizer</p> <p>6 - Sprayers</p> <p>7 - Harvesters</p> <p>8 - Root Harvester</p> <p>9 - Forage harvester</p> <p>10 - Irrigation</p> <p>11 - Transport / Trailers</p> <p>12 - Farmyard Work</p> <p>13 - Powered Auxiliary Units</p> <p>14 - Special Crops</p> <p>17 - Sensor System</p> <p>25 - Slurry Applicators</p>
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>515 - Tramline Control State</b>
------------------	-------------------------------------

Definition	<p>Specifies the actual state of Tramline Control.</p> <p>The value definitions are:</p> <p>Byte 1 Bits 0-1 = 00 manual/off</p> <p>Byte 1 Bits 0-1 = 01 automatic/on</p> <p>Byte 1 Bits 0-1 = 10 error</p> <p>Byte 1 Bits 0-1 = 11 undefined/not supported</p> <p>Byte 1 Bits 2-7 reserved, set to 0.</p> <p>The DDI shall support the OnChange trigger so that the Task Controller is able to get informed when the value gets changed by the Working Set Master. The Task Controller shall activate this trigger when using the DDI.</p>
Comment	<p>The Tramline Control State has the same purpose and definition like the Section Control State DDI 160.</p> <p>For more details see also attachment on DDI 505.</p>
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 3
Display Range	0 - 3
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>516 - Tramline Overdosing Rate</b>
Definition	Overdosing Rate for the rows adjacent to the Tramline Track.
Comment	<p>This DDI specifies the Overdosing Rate for the rows adjacent to the Tramline Tracks. This value is specified in ppm. The value 1.000.000 (100%) is the normal rate. A value &gt; 100% means that a overdosing is applied.</p> <p>In case of a seeding distance, the implement should calculate the overdosing based on seeds per area and recalculate that value to an overdosing seeding rate.</p> <p>Background: If the seeding distance is just multiplied with the overdosing rate, the seeding distance will increase which leads to less seed on the field!</p> <p>Example: In the case the seeding distance is specified the overdosing rate will result in a shorter seed distance. A seeding distance of 20,00 cm with an overdosing rate of 110% will result in a seed distance of 18,18cm for the rows adjacent to the Tramline Tracks.</p> <p>For more details see also attachment on DDI 505.</p>
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	ppm - Parts per million
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>517 - Setpoint Tramline Condensed Work State 1-16</b>
------------------	--

Definition	The Setpoint Tramline Condensed Work State DDIs are the control command counterparts to the Actual Tramline Condensed Work States DDIs. The value is a combination of the Setpoint Tramline Valve Work States of individual Tramline Valves number 1 to 16 into a single Setpoint Tramline Condensed Work State of their parent DeviceElement. The Setpoint Tramline Condensed Work State contains the child element Setpoint Tramline Work States, in the driving direction from left to right, where the leftmost child element Setpoint Tramline Work State are the 2 lowest significant bits of the Process Data Value. Each child device elements Setpoint Work State is represented by 2 bits and defined as: 00 = disable/off, 01 = enable/on, 10 = error indicator, 11 = no change. In total 16 child device element Setpoint Tramline Work States can be contained in one Setpoint Tramline Condensed Work State of their parent DeviceElement. If less than 16 child device element Setpoint Tramline Work States are available, then the unused bits shall be set to value 11 (no change).
Comment	The Setpoint Tramline Condensed Work State 1-16 has the same purpose and definition like the Setpoint Condensed Work State 1-16 DDI 290.  For more details see also attachment on DDI 505.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>518 - Actual Tramline Condensed Work State 1-16</b>
Definition	Combination of the Actual States of individual Tramline Valves number 1 to 16 into a single Actual Tramline State of their parent DeviceElement. The Actual Tramline Condensed Work State contains the child element Actual Tramline Work States, in the driving direction from left to right, where the leftmost child element Actual Tramline Work State are the 2 lowest significant bits of the Process Data Value. Each child device elements Actual Tramline Work State is represented by 2 bits and defined as: 00 = disabled/off, 01 = enabled/on, 10 = error indicator, 11 = undefined/not installed. In total 16 child device element Actual Tramline Work States can be contained in one Actual Tramline Condensed Work State of their parent DeviceElement. If less than 16 child device element Actual Tramline Work States are available, then the unused bits shall be set to value 11 (not installed).
Comment	The Actual Tramline Condensed Work State 1-16 has the same purpose and definition like the Actual Condensed Work State 1-16 DDI 161.  For more details see also attachment on DDI 505.
Typically used by Device Class(es)	4 - Planters /Seeders
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 4294967295
Display Range	0 - 4294967295
Submit by	Karsten Helweg
Submit Date	2015-12-10
Submit Company	Competence Center ISOBUS e.V.
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-01
Status Comments	

<b>DD Entity</b>	<b>519 - Last Bale Lifetime Count</b>
Definition	The Lifetime Bale Count of the bale that leaves the machine. The value shall be equal to the Lifetime Bale Count that was reported when this bale is knotted.

Comment	The recommended use of this DDE is for a baler to report this once for every bale that leaves the machine. A baler can add this to its default set of data, based on an internal on-change data trigger that causes the baler to report the value of this DDE when the bale leaves the machine. The recommendation for data logging is that all "Last Bale" DDEs that are supported by a device are reported together at the moment that the bale leaves the machine. The value shall be equal to the Lifetime Bale Count that was reported when this bale is knotted.
Typically used by Device Class(es)	7 - Harvesters 8 - Root Harvester 9 - Forage harvester
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2016-06-06
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2016-09-19
Status Comments	



<b>DD Entity</b>	<b>520 - Actual Canopy Height</b>
Definition	Actual height of the canopy above ground.
Comment	
Typically used by Device Class(es)	5 - Fertilizer 6 - Sprayers 9 - Forage harvester 14 - Special Crops 17 - Sensor System
Unit Symbol	mm - Length
Resolution	1
SAE SPN	
CANBus Range	0 - 0
Display Range	0 - 2147483647
Submit by	Joe Tevis
Submit Date	2016-10-04
Submit Company	Topcon Precision Ag
Revision Number	1
Current Status	ISO-Published
Status Date	2016-11-15
Status Comments	

<b>DD Entity</b>	<b>521 - GNSS Installation Type</b>
Definition	<p>The GNSS Installation Type DDE is used by the device to provide additional information about the type and location of the GPS receiver with reference to the overall system.</p> <p>Additional information are required especially when more than one GNSS receiver is installed on the system.</p> <p>The GPS Installation Type value is an instance enumeration with the following definitions:</p> <ul style="list-style-type: none"> <li>0 = Unknown</li> <li>1 = Tractor integrated antenna</li> <li>2 = Tractor universal antenna (removable)</li> <li>3 = First Implement antenna</li> <li>4 = Second Implement antenna</li> <li>5 = Display integrated antenna</li> <li>6 to 100 Reserved</li> </ul>
Comment	<p>Today some devices are equipped with more than one GPS receivers for certain applications. In this case both do have different offset defined and therefore an application need to be able to identify each receiver clearly. This DDI does provide the possibility to add these additional information below the appropriate device element.</p>

Typically used by Device Class(es)	1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxiliary Units 14 - Special Crops 15 - Municipal Work 17 - Sensor System 18 - Reserved for Future Assignment 19 - Timber Harvesters 20 - Forwarders 21 - Timber loaders 22 - Timber Processing Machines 23 - Mulchers 24 - Utility Vehicles 25 - Slurry Applicators 26 - Feeder / Mixer
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	0 - 100
Display Range	0 - 100
Submit by	Meyer Matthias
Submit Date	2016-10-17
Submit Company	John Deere
Revision Number	1
Current Status	ISO-Published
Status Date	2016-11-28
Status Comments	

<b>DD Entity</b>	<b>522 - Twine Bale Total Count</b>
Definition	The total number of twine bound product units for which Twine binding method was used during operation.
Comment	Twine Total Count can be used as total counter of a device element. It is intended to be used as task based and therefore it is recommended to support the on-time and on-change trigger methods.  The total trigger method and the setable property are required for this DDE.
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Elshout
Submit Date	2017-01-26
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2017-02-04
Status Comments	

<b>DD Entity</b>	<b>523 - Mesh Bale Total Count</b>
Definition	The total number of mesh product units for which Net binding method was used during operation.
Comment	Twine Total Count can be used as total counter of a device element. It is intended to be used as task based and therefore it is recommended to support the on-time and on-change trigger methods.  The total trigger method and the setable property are required for this DDE.
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Elshout
Submit Date	2017-01-26
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2017-02-04
Status Comments	

<b>DD Entity</b>	<b>524 - Lifetime Twine Bale Total Count</b>
Definition	Entire total number of twine bound product units for which Twine binding method was used during operation, of a device lifetime
Comment	This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be settable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value. The Working Set Master shall support the total trigger method for this DDE but shall not support the settable property. The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Elshout
Submit Date	2017-01-26
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2017-02-04
Status Comments	

<b>DD Entity</b>	<b>525 - Lifetime Mesh Bale Total Count</b>
Definition	Entire total number of mesh product units for which Net binding method was used during operation, of a device lifetime
Comment	This is the overall total of the device. This total does not refer to an application controlled by a Task Controller. Therefore this DDE shall not be settable within the device description and neither shall the device reset the value when the task status changed. It is up to the device control system when to reset this value. The Working Set Master shall support the total trigger method for this DDE but shall not support the settable property. The Task Controller can request and store this DDE at the end of a task. But it shall not set this DDE when the task is resumed.
Typically used by Device Class(es)	9 - Forage harvester
Unit Symbol	# - Quantity/Count
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Elshout

Submit Date	2017-01-26
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Published
Status Date	2017-02-04
Status Comments	

<b>DD Entity</b>	<b>526 - Actual Cooling Fluid Temperature</b>
Definition	The actual temperature of the cooling fluid for the machine.
Comment	The addition of a DDI for such values allows such values to be added to the default data set that devices present to a task controller or a data logger. If not specially defined within a certain function the assumption is that this DDI represents the engine cooling fluid temperature.
Typically used by Device Class(es)	<ul style="list-style-type: none"> <li>- Not Assigned</li> <li>0 - Non-specific system</li> <li>1 - Tractor</li> <li>2 - Primary Soil Tillage</li> <li>3 - Secondary Soil Tillage</li> <li>4 - Planters /Seeders</li> <li>5 - Fertilizer</li> <li>6 - Sprayers</li> <li>7 - Harvesters</li> <li>8 - Root Harvester</li> <li>9 - Forage harvester</li> <li>10 - Irrigation</li> <li>11 - Transport / Trailers</li> <li>12 - Farmyard Work</li> <li>13 - Powered Auxiliary Units</li> <li>14 - Special Crops</li> <li>15 - Municipal Work</li> <li>17 - Sensor System</li> <li>18 - Reserved for Future Assignment</li> <li>19 - Timber Harvesters</li> <li>20 - Forwarders</li> <li>21 - Timber loaders</li> <li>22 - Timber Processing Machines</li> <li>23 - Mulchers</li> <li>24 - Utility Vehicles</li> <li>25 - Slurry Applicators</li> <li>26 - Feeder / Mixer</li> </ul>
Unit Symbol	mK - Temperature
Resolution	1
SAE SPN	
CANBus Range	0 - 2147483647
Display Range	0 - 2147483647
Submit by	Frank Wiebeler
Submit Date	2016-04-01
Submit Company	Maschinenfabrik Bernard Krone
Revision Number	1
Current Status	ISO-Published
Status Date	2017-06-12
Status Comments	

<b>DD Entity</b>	<b>57342 - PGN Based Data</b>
Definition	This DDI is used in the XML files to identify PGN based data.
Comment	This DDI is specified in ISO 11783-10 IS paragraph 6.3 Logging parameters from parameter groups.
Typically used by Device Class(es)	0 - Non-specific system 1 - Tractor 2 - Primary Soil Tillage 3 - Secondary Soil Tillage 4 - Planters /Seeders 5 - Fertilizer 6 - Sprayers 7 - Harvesters 8 - Root Harvester 9 - Forage harvester 10 - Irrigation 11 - Transport / Trailers 12 - Farmyard Work 13 - Powered Auxilary Units 14 - Special Crops 15 - Municipal Work
Unit Symbol	n.a. -
Resolution	1
SAE SPN	
CANBus Range	-2147483648 - 2147483647
Display Range	-2147483648 - 2147483647
Submit by	Part 10 Task Force
Submit Date	2005-01-25
Submit Company	0 - Reserved
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	Added to the on-line database

<b>DD Entity</b>	<b>57343 - Request Default Process Data</b>
Definition	Request Default Process Data. This DDE is the highest ISO assigned entity. The range above this number is reserved for manufacture specific DDE's.
Comment	This DDE was a result of Jan 2005 Task Controller meeting.
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	n.a. -
Resolution	1
SAE SPN	not specified
CANBus Range	0 - 0
Display Range	0 - 0
Submit by	11783-Part 10 Task Force
Submit Date	2005-01-20
Submit Company	89 - Kverneland Group, Electronics Division
Revision Number	1
Current Status	ISO-Approved
Status Date	2009-02-05
Status Comments	Updated description, added reference to ISO11783-10

<b>DD Entity</b>	<b>57344 - 65534 Proprietary DDI Range</b>
Definition	Manufacturer proprietary definitions
Comment	It is not recommended to process proprietary DDEs from other manufacturers
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	n.a. -
Resolution	0
SAE SPN	
CANBus Range	-
Display Range	-
Submit by	Part 10 Task Force
Submit Date	0000-00-00
Submit Company	0 - Reserved
Revision Number	1



<b>DD Entity</b>	<b>65535 - Reserved</b>
Definition	Reserved
Comment	
Typically used by Device Class(es)	- Not Assigned
Unit Symbol	n.a. -
Resolution	0
SAE SPN	
CANBus Range	-
Display Range	-
Submit by	Part 10 Task Force
Submit Date	0000-00-00
Submit Company	0 - Reserved
Revision Number	1